

屋内照明器具特性

品番 (品名)	XS Z D 1 0 6 1 V	
光源	LLD2411VCB1 ×1	500.0 l m
管理番号	K0191443 (0) DB 1	
B Z 分類	B Z 1	

器具効率	95 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束		0 %	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束	95 %	床	10 %				10 %				10 %				10 %				0 %	
室指数	照明率 (X 0.01)																			Z C M
保守率	良	0.67	0.6	85	80	77	75	84	80	77	75	83	79	77	75	82	79	76	75	74
	中	0.63	0.8	89	85	82	80	88	85	82	80	87	84	82	80	86	83	81	79	79
	否	0.56	1.0	92	88	86	84	91	88	85	83	90	87	85	83	89	86	84	83	82
下方投影面積	等価発光面積	c m ²	1.25	94	91	89	87	93	90	88	86	92	89	87	86	91	88	87	85	84
			1.5	96	93	91	89	95	92	90	88	93	91	89	88	92	90	88	87	86
取付高さ	器具間隔最大限		2.5	99	97	95	94	98	96	94	93	96	95	93	92	94	93	92	91	89
	横方向 (A)	縦方向 (B)	3.0	99	98	96	95	99	97	96	94	97	95	94	93	95	94	93	92	90
H m	0.83 H m	0.83 H m	4.0	100	99	98	97	99	98	97	96	98	97	96	95	96	95	94	94	91
			5.0	101	100	99	98	100	99	98	97	98	97	96	96	96	96	95	94	94
			7.0	102	101	100	99	101	100	99	99	99	98	97	97	96	96	95	93	
			10.0	102	102	101	100	101	101	100	100	99	99	98	98	97	97	96	94	

