

屋内照明器具特性

品番 (品名)	YYY83154+YYY95020									
光源	LED3000_85_465 x1 465.0 lm									
管理番号	K0192437 (0) DB 1									
BZ分類	BZ10									

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
上方光束 下方光束		7 4 % 2 6 %	室指数	照明率 (X 0 . 0 1)																	Z C M
保守率		良 中 否	0 . 8 3	0 . 6	4 2	3 1	2 3	1 8	3 7	2 7	2 1	1 6	2 8	2 0	1 5	1 2	1 9	1 4	1 0	8	1
			0 . 8 1	0 . 8	5 0	3 9	3 1	2 5	4 4	3 4	2 7	2 2	3 3	2 6	2 0	1 7	2 3	1 8	1 4	1 1	2
			0 . 7 7	1 . 0	5 6	4 5	3 7	3 1	4 9	4 0	3 3	2 7	3 7	3 0	2 5	2 1	2 5	2 1	1 7	1 4	3
				1 . 2 5	6 1	5 1	4 3	3 7	5 4	4 5	3 8	3 3	4 0	3 4	2 9	2 5	2 8	2 3	2 0	1 7	5
下方投影面積		c m ²	1 . 5	6 5	5 5	4 8	4 2	5 7	4 9	4 3	3 7	4 3	3 7	3 2	2 8	3 0	2 6	2 2	2 0	6	
等価発光面積	c m ²		2 . 0	7 0	6 2	5 5	5 0	6 2	5 5	4 9	4 4	4 7	4 2	3 8	3 4	3 3	2 9	2 6	2 4	8	
取付 高さ	器具間隔最大限		2 . 5	7 4	6 7	6 0	5 5	6 6	5 9	5 4	4 9	5 0	4 5	4 1	3 8	3 5	3 2	2 9	2 7	1 0	
	横方向 (A) 縦方向 (B)		3 . 0	7 6	7 0	6 4	5 9	6 8	6 2	5 7	5 3	5 2	4 8	4 4	4 1	3 7	3 4	3 1	2 9	1 1	
H m	0 . 0 0 H m	0 . 2 0 H m	4 . 0	8 0	7 4	6 9	6 5	7 1	6 6	6 2	5 8	5 4	5 1	4 8	4 5	3 9	3 6	3 4	3 2	1 3	
			5 . 0	8 2	7 7	7 3	6 9	7 3	6 9	6 5	6 2	5 6	5 3	5 1	4 8	4 0	3 8	3 6	3 4	1 4	
			7 . 0	8 4	8 1	7 7	7 4	7 5	7 2	6 9	6 7	5 8	5 6	5 4	5 2	4 2	4 1	3 9	3 7	1 6	
			1 0 . 0	8 6	8 4	8 1	7 9	7 7	7 5	7 3	7 1	6 0	5 8	5 7	5 5	4 4	4 3	4 1	4 0	1 8	

