

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | XND7569SL                    |
| 光源       | LED3000_80_7705 ×1 7705.0 lm |
| 管理番号     | K0179583 ( 1 ) DB 1          |
| BZ分類     | BZ1                          |

| 器具効率         |                          | 100 %           | 反射率             | 天井            | 80 % |     |     |     | 70 % |     |     |     | 50 % |     |     |     | 30 % |     |    |    | 0 %  |  |
|--------------|--------------------------|-----------------|-----------------|---------------|------|-----|-----|-----|------|-----|-----|-----|------|-----|-----|-----|------|-----|----|----|------|--|
|              |                          |                 |                 | 壁             | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50  | 30 | 10 | 0 %  |  |
|              |                          |                 |                 | 床             | 10 % |     |     |     | 10 % |     |     |     | 10 % |     |     |     | 10 % |     |    |    | 0 %  |  |
| 上方光束<br>下方光束 |                          | 100 %           | 室指数             | 照明率 ( X0.01 ) |      |     |     |     |      |     |     |     |      |     |     |     |      |     |    |    | Z CM |  |
| 保守率          |                          | 良<br>中<br>否     | 0.76            | 0.6           | 74   | 66  | 61  | 57  | 73   | 65  | 60  | 57  | 71   | 65  | 60  | 57  | 70   | 64  | 60 | 57 | 55   |  |
|              |                          |                 | 0.72            | 0.8           | 83   | 76  | 71  | 67  | 82   | 75  | 71  | 67  | 80   | 74  | 70  | 67  | 78   | 73  | 70 | 67 | 65   |  |
|              |                          |                 | 1.0             | 88            | 82   | 77  | 74  | 87  | 81   | 77  | 74  | 85  | 80   | 76  | 74  | 84  | 79   | 76  | 73 | 72 |      |  |
|              |                          |                 | 0.64            | 1.25          | 93   | 87  | 83  | 80  | 92   | 86  | 83  | 80  | 89   | 85  | 82  | 79  | 88   | 84  | 81 | 79 | 77   |  |
| 下方投影面積       |                          | cm <sup>2</sup> | 1.5             | 95            | 90   | 87  | 84  | 94  | 90   | 86  | 83  | 92  | 88   | 85  | 83  | 90  | 87   | 84  | 82 | 80 |      |  |
| 等価発光面積       |                          |                 | cm <sup>2</sup> | 2.0           | 99   | 95  | 92  | 89  | 98   | 94  | 91  | 89  | 95   | 92  | 90  | 88  | 93   | 91  | 89 | 87 | 85   |  |
| 取付<br>高さ     | 器具間隔最大限                  |                 | 2.5             | 101           | 97   | 95  | 92  | 100 | 97   | 94  | 92  | 97  | 95   | 93  | 91  | 95  | 93   | 91  | 90 | 88 |      |  |
|              | 横方向 ( A )      縦方向 ( B ) |                 | 3.0             | 102           | 99   | 97  | 95  | 101 | 98   | 96  | 94  | 99  | 97   | 95  | 93  | 97  | 95   | 93  | 92 | 90 |      |  |
| H m          | 1.02 H m                 | 1.02 H m        | 4.0             | 104           | 101  | 100 | 98  | 103 | 101  | 99  | 97  | 100 | 99   | 97  | 96  | 98  | 97   | 96  | 94 | 92 |      |  |
|              |                          |                 | 5.0             | 105           | 103  | 101 | 100 | 103 | 102  | 100 | 99  | 101 | 100  | 99  | 97  | 99  | 98   | 97  | 96 | 94 |      |  |
|              |                          |                 | 7.0             | 106           | 104  | 103 | 102 | 105 | 103  | 102 | 101 | 102 | 101  | 100 | 100 | 100 | 99   | 99  | 98 | 95 |      |  |
|              |                          |                 | 10.0            | 107           | 106  | 105 | 104 | 105 | 105  | 104 | 103 | 103 | 102  | 102 | 101 | 101 | 100  | 100 | 99 | 97 |      |  |

