

屋内照明器具特性

品番 (品名)	XS Z B 1 0 0 0 2									
光源	LLD2411LCB1 ×1					500.0 l m				
管理番号	K0193247 (3) DB 1									
B Z 分類	BZ1 / 0.9 / BZ2 / 2.8 / BZ3									

器具効率	87 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		14 %	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		73 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.63	0.6	0.6	5.9	5.1	4.6	4.3	5.7	5.0	4.6	4.2	5.4	4.8	4.4	4.2	5.2	4.7	4.3	4.1	3.8
	中	0.6	0.6	0.6	6.5	5.8	5.3	5.0	6.4	5.7	5.2	4.9	6.0	5.5	5.1	4.8	5.7	5.2	4.9	4.6	4.4
	否	0.56	0.56	0.56	7.0	6.3	5.8	5.4	6.8	6.1	5.7	5.4	6.4	5.9	5.5	5.2	6.0	5.6	5.3	5.0	4.7
					7.3	6.7	6.3	5.9	7.1	6.6	6.1	5.8	6.7	6.2	5.9	5.6	6.3	6.0	5.7	5.4	5.1
下方投影面積	c m ²		1.25	7.3	6.7	6.3	5.9	7.1	6.6	6.1	5.8	6.7	6.2	5.9	5.6	6.3	6.0	5.7	5.4	5.1	
	等価発光面積		c m ²	1.5	7.6	7.0	6.6	6.2	7.4	6.9	6.5	6.1	6.9	6.5	6.2	5.9	6.5	6.2	5.9	5.7	5.3
取付高さ	器具間隔最大限		2.5	8.1	7.7	7.4	7.1	7.9	7.5	7.2	6.9	7.4	7.1	6.9	6.7	7.0	6.8	6.6	6.4	5.9	
	横方向 (A)	縦方向 (B)	3.0	8.3	7.9	7.6	7.4	8.0	7.7	7.4	7.2	7.6	7.3	7.1	6.9	7.1	6.9	6.7	6.6	6.1	
H m	0.77 H m	0.77 H m	4.0	8.5	8.2	7.9	7.7	8.2	8.0	7.7	7.5	7.7	7.5	7.3	7.2	7.3	7.1	7.0	6.8	6.3	
			5.0	8.6	8.4	8.1	7.9	8.3	8.1	7.9	7.7	7.9	7.7	7.5	7.4	7.4	7.3	7.1	7.0	6.4	
			7.0	8.7	8.6	8.4	8.2	8.5	8.3	8.2	8.0	8.0	7.9	7.7	7.6	7.5	7.4	7.3	7.2	6.6	
			10.0	8.8	8.7	8.6	8.5	8.6	8.5	8.3	8.2	8.1	8.0	7.9	7.8	7.6	7.5	7.5	7.4	6.8	

