

屋内照明器具特性

品番 (品名)	XS Z B 1 0 0 1 4	
光源	LLD2411LCB1 ×1	500.0 l m
管理番号	K0193681 (0) DB 1	
B Z 分類	BZ1 / 4.5 / BZ2	

器具効率	99 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		7 %	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
下方光束	92 %	床	10 %				10 %				10 %				10 %				0 %		
室指数	照明率 (X 0.01)																				Z C M
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	
下方投影面積	等価発光面積	c m ²		1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	89	92	95	97	98	100	101	102	103
		c m ²		89	92	95	97	98	100	101	102	103									
取付高さ	器具間隔最大限		H m		0.74 H m	0.74 H m	0.74 H m	0.74 H m	0.74 H m	0.74 H m	0.74 H m	0.74 H m	0.74 H m	0.74 H m	0.74 H m	0.74 H m	0.74 H m	0.74 H m	0.74 H m	0.74 H m	
	横方向 (A)	縦方向 (B)	0.74 H m	0.74 H m	0.74 H m	0.74 H m	0.74 H m	0.74 H m	0.74 H m	0.74 H m	0.74 H m	0.74 H m	0.74 H m	0.74 H m	0.74 H m	0.74 H m	0.74 H m	0.74 H m	0.74 H m	0.74 H m	

