

| 屋内照明器具特性                 |                                    |                                       |                         |      |    |    |      |      |    |    |      |      |    |    |      |      |    |    |     |     |
|--------------------------|------------------------------------|---------------------------------------|-------------------------|------|----|----|------|------|----|----|------|------|----|----|------|------|----|----|-----|-----|
| 品番 ( 品名 )                |                                    | YYY46024Z+YYY96222Z_FRON              |                         |      |    |    |      |      |    |    |      |      |    |    |      |      |    |    |     |     |
| 光源                       |                                    | LED4000_70_2250 ×1 2250.0 lm          |                         |      |    |    |      |      |    |    |      |      |    |    |      |      |    |    |     |     |
| 管理番号                     |                                    | K0148446 ( 0 ) DB 1                   |                         |      |    |    |      |      |    |    |      |      |    |    |      |      |    |    |     |     |
| B Z 分類                   |                                    | BZ5/0.7/BZ7/0.9/BZ8/1.1/BZ9 / 1.4/BZ1 |                         |      |    |    |      |      |    |    |      |      |    |    |      |      |    |    |     |     |
| 器具効率<br><br>上方光束<br>下方光束 | 100 %<br><br>100 %<br>0 %          | 反射率                                   | 天井                      | 80 % |    |    |      | 70 % |    |    |      | 50 % |    |    |      | 30 % |    |    |     | 0 % |
|                          | 壁                                  |                                       | 70                      | 50   | 30 | 10 | 70   | 50   | 30 | 10 | 70   | 50   | 30 | 10 | 70   | 50   | 30 | 10 | 0 % |     |
|                          | 床                                  |                                       | 10 %                    |      |    |    | 10 % |      |    |    | 10 % |      |    |    | 10 % |      |    |    | 0 % |     |
|                          | 室指数                                |                                       | 照明率 ( X0.01 ) ZCM       |      |    |    |      |      |    |    |      |      |    |    |      |      |    |    |     |     |
| 保守率                      | 良 0.69<br>中 0.67<br>否 0.63         | 0.6                                   | 43                      | 33   | 26 | 22 | 37   | 28   | 23 | 19 | 25   | 19   | 16 | 13 | 14   | 11   | 9  | 8  | 0   |     |
|                          | 0.8                                | 51                                    | 41                      | 34   | 29 | 43 | 35   | 29   | 25 | 29 | 24   | 21   | 18 | 17 | 14   | 12   | 11 |    | 0   |     |
|                          | 1.0                                | 56                                    | 47                      | 40   | 35 | 48 | 40   | 35   | 31 | 33 | 28   | 24   | 22 | 19 | 16   | 14   | 13 |    | 0   |     |
|                          | 1.25                               | 61                                    | 53                      | 47   | 42 | 52 | 46   | 40   | 36 | 36 | 31   | 28   | 25 | 20 | 18   | 16   | 15 |    | 0   |     |
| 下方投影面積<br>等価発光面積         | cm <sup>2</sup><br>cm <sup>2</sup> | 1.5                                   | 65                      | 57   | 51 | 46 | 56   | 49   | 44 | 40 | 38   | 34   | 31 | 28 | 22   | 20   | 18 | 17 | 0   |     |
|                          |                                    | 2.0                                   | 70                      | 63   | 58 | 54 | 60   | 55   | 50 | 47 | 41   | 38   | 35 | 33 | 24   | 22   | 21 | 19 | 0   |     |
| 取付高さ                     | 器具間隔最大限                            |                                       | 2.5                     | 73   | 67 | 63 | 59   | 63   | 58 | 54 | 51   | 43   | 40 | 38 | 36   | 25   | 23 | 22 | 21  | 0   |
|                          | 横方向 ( A )                          | 縦方向 ( B )                             | 3.0                     | 75   | 70 | 66 | 62   | 64   | 61 | 57 | 54   | 44   | 42 | 40 | 38   | 26   | 24 | 23 | 22  | 0   |
| H m                      | 0.00 H m                           | 0.00 H m                              | 4.0                     | 78   | 74 | 71 | 67   | 67   | 64 | 61 | 59   | 46   | 44 | 43 | 41   | 27   | 26 | 25 | 24  | 0   |
|                          |                                    |                                       | 5.0                     | 79   | 76 | 73 | 71   | 68   | 66 | 63 | 61   | 47   | 46 | 44 | 43   | 27   | 27 | 26 | 25  | 0   |
|                          |                                    |                                       | 7.0                     | 81   | 79 | 77 | 75   | 70   | 68 | 66 | 65   | 49   | 47 | 46 | 45   | 28   | 28 | 27 | 27  | 0   |
|                          |                                    |                                       | 10.0                    | 83   | 81 | 80 | 78   | 72   | 70 | 69 | 68   | 50   | 49 | 48 | 47   | 29   | 28 | 28 | 28  | 0   |
| 配光曲線<br>ランプ光束1000 lm     |                                    |                                       | 直射水平面照度<br>ランプ光束1000 lm |      |    |    |      |      |    |    |      |      |    |    |      |      |    |    |     |     |
|                          |                                    |                                       |                         |      |    |    |      |      |    |    |      |      |    |    |      |      |    |    |     |     |
| A 3.0° 0° A' 3.0°        |                                    |                                       | 8m 6 4 2 0 2 4 6 8 A'   |      |    |    |      |      |    |    |      |      |    |    |      |      |    |    |     |     |
|                          |                                    |                                       |                         |      |    |    |      |      |    |    |      |      |    |    |      |      |    |    |     |     |