

# 屋内照明器具特性

品番 (品名)	XS Z B 1 0 1 1 9									
光源	LLD2401VCB1 ×1					500.0 l m				
管理番号	K0193687 ( 0 ) DB 1									
B Z 分類	B Z 4 / 0 . 7 / B Z 3 / 0 . 9 / B Z 4 / 6 . 0 / B Z 5									

器具効率	89 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束		11 %	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束	78 %	床	10 %				10 %				10 %				10 %				0 %	
室指数			照明率 ( X 0 . 0 1 )																Z C M	
保守率	良	0.63	0.6	53	43	37	33	51	42	36	32	48	41	35	32	45	39	34	31	28
	中	0.6	0.8	61	52	46	41	59	51	45	41	56	49	44	40	53	47	42	39	36
	否	0.56	1.0	67	58	52	48	65	57	51	47	61	54	49	46	57	52	48	44	41
			1.25	71	64	58	53	69	62	57	53	65	59	55	51	61	56	53	49	46
下方投影面積		c m <sup>2</sup>	1.5	75	68	62	58	72	66	61	57	68	63	58	55	64	60	56	53	49
等価発光面積		c m <sup>2</sup>	2.0	79	73	68	64	77	71	67	63	72	68	64	61	68	64	61	59	54
取付高さ	器具間隔最大限		2.5	82	76	72	68	79	75	71	67	75	71	68	65	70	67	65	62	58
	横方向 ( A )	縦方向 ( B )	3.0	83	79	75	72	81	77	73	70	77	73	70	68	72	70	67	65	60
H m	1.05 H m	0.49 H m	4.0	86	82	79	76	83	80	77	75	79	76	74	72	75	72	70	69	64
			5.0	87	84	82	79	85	82	80	77	80	78	76	74	76	74	73	71	66
			7.0	89	87	85	83	87	85	83	81	82	80	79	77	78	76	75	74	69
			10.0	90	89	87	86	88	87	85	84	84	82	81	80	79	78	77	76	71

