

屋内照明器具特性

| | | |
|---------|---------------------|-----------|
| 品番 (品名) | XS Z B 1 0 1 2 5 | |
| 光源 | LLD2411VCB1 ×1 | 500.0 l m |
| 管理番号 | K0193681 (0) DB 1 | |
| B Z 分類 | BZ1 / 4.5 / BZ2 | |

| | | | | | | | | | | | | | | | | | | | | | |
|------------------|------------------|----------------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|-----|
| 器具効率 | 99 % | 天井 | 80 % | | | | 70 % | | | | 50 % | | | | 30 % | | | | 0 % | | |
| | 上方光束 7 % | | 反射率 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0 % | |
| 下方光束 92 % | | 床 | | 10 % | | | | 10 % | | | | 10 % | | | | 10 % | | | | 0 % | |
| 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | | | | | ZCM |
| 保守率 | 良 | 0.63 | 0.6 | 0.6 | 0.6 | 0.6 | 0.6 | 0.6 | 0.6 | 0.6 | 0.6 | 0.6 | 0.6 | 0.6 | 0.6 | 0.6 | 0.6 | 0.6 | 0.6 | 0.6 | |
| | 中 | 0.6 | 0.6 | 0.6 | 0.6 | 0.6 | 0.6 | 0.6 | 0.6 | 0.6 | 0.6 | 0.6 | 0.6 | 0.6 | 0.6 | 0.6 | 0.6 | 0.6 | 0.6 | 0.6 | |
| | 否 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | |
| 下方投影面積 等価発光面積 | c m ² | | 1.25 | 1.5 | 2.0 | 2.5 | 3.0 | 4.0 | 5.0 | 7.0 | 10.0 | 10.0 | 10.0 | 10.0 | 10.0 | 10.0 | 10.0 | 10.0 | 10.0 | 10.0 | |
| | c m ² | | 1.5 | 2.0 | 2.5 | 3.0 | 4.0 | 5.0 | 7.0 | 10.0 | 10.0 | 10.0 | 10.0 | 10.0 | 10.0 | 10.0 | 10.0 | 10.0 | 10.0 | 10.0 | |
| 取付 高さ | 器具間隔最大限 | | 2.5 | 3.0 | 4.0 | 5.0 | 7.0 | 10.0 | 10.0 | 10.0 | 10.0 | 10.0 | 10.0 | 10.0 | 10.0 | 10.0 | 10.0 | 10.0 | 10.0 | 10.0 | |
| | 横方向 (A) H m | 縦方向 (B) H m | 0.74 H m | 0.74 H m | 0.74 H m | 0.74 H m | 0.74 H m | 0.74 H m | 0.74 H m | 0.74 H m | 0.74 H m | 0.74 H m | 0.74 H m | 0.74 H m | 0.74 H m | 0.74 H m | 0.74 H m | 0.74 H m | 0.74 H m | 0.74 H m | |

