

屋内照明器具特性	
品番 (品名)	XS Z B 1 0 1 6 7
光源	LLD2401VCB1 ×1                      500.0 1 m
管理番号	K0193060 ( 0 ) DB 1
B Z 分類	BZ6

器具効率	82 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	25 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	57 %	室指数	照明率 ( X0.01 )																ZCM	
保守率	良 中 否 0.63 0.6 0.56	0.6	42	32	26	21	40	31	25	21	35	28	23	19	31	25	21	18	15	
		0.8	49	39	33	28	46	37	31	27	41	34	29	25	36	31	26	23	19	
		1.0	54	44	38	33	51	42	36	32	45	38	33	29	40	34	30	27	22	
		1.25	58	50	43	38	55	47	41	37	49	42	38	34	43	38	34	31	26	
下方投影面積	c m <sup>2</sup>	1.5	61	53	47	42	58	51	45	41	51	46	41	37	46	41	37	34	28	
		2.0	66	59	53	48	62	56	51	46	55	50	46	43	49	45	42	39	32	
取付高さ	器具間隔最大限		2.5	68	62	57	53	65	59	55	51	58	54	50	46	52	48	45	42	35
	横方向 (A)	縦方向 (B)	3.0	71	65	60	56	67	62	58	54	60	56	52	49	53	50	47	45	38
H m	0.94 H m	0.94 H m	4.0	73	69	65	61	70	65	62	59	62	59	56	54	56	53	51	49	41
			5.0	75	71	68	64	71	68	65	62	64	61	59	56	57	55	53	51	43
			7.0	77	74	71	69	73	71	68	66	66	64	62	60	59	58	56	54	46
			10.0	79	76	74	72	75	73	71	69	68	66	65	63	61	60	58	57	48

