

屋内照明器具特性	
品番 (品名)	XND2037SFK
光源	LED2700_85_1455 ×1 1455.0 lm
管理番号	K0176632 (0) DB 1
BZ分類	BZ1

器具効率		100 % 上方光束 0 % 下方光束 100 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
				室指数	照明率 (X0.01) ZCM																				
保守率		良 中 否	0.81	0.6	75	67	62	58	74	67	62	58	73	66	61	58	71	65	61	58	57				
			0.77	0.8	84	77	72	69	83	77	72	69	81	76	72	69	80	75	71	68	67				
			0.68	1.0	89	83	79	76	88	83	79	76	86	82	78	75	85	80	77	75	73				
			0.68	1.25	93	88	84	81	92	87	84	81	90	86	83	80	88	85	82	80	78				
下方投影面積		cm ²	1.5	96	91	88	85	95	91	87	85	93	89	86	84	91	88	85	83	82					
等価発光面積			2.0	99	95	92	90	98	95	92	89	96	93	91	89	94	92	90	88	86					
取付高さ	器具間隔最大限		2.5	101	98	95	93	100	97	95	93	98	95	93	92	96	94	92	91	89					
	横方向 (A) 縦方向 (B)		3.0	102	100	97	95	101	99	97	95	99	97	95	94	97	95	94	92	90					
H m	1.02 H m	1.02 H m	4.0	104	102	100	98	103	101	99	97	100	99	97	96	98	97	96	95	93					
			5.0	105	103	101	100	103	102	101	99	101	100	99	98	99	98	97	96	94					
			7.0	106	104	103	102	104	103	102	101	102	101	100	100	100	99	99	98	95					
			10.0	106	105	105	104	105	104	104	103	103	102	102	101	101	100	100	99	97					

