

# 屋内照明器具特性

品番 (品名)	XS Z B 1 0 2 3 5	
光源	LLD2411VCB1 ×1	500.0 l m
管理番号	K0193681 ( 0 ) DB 1	
B Z 分類	BZ1 / 4.5 / BZ2	

器具効率	99 %	天井	80 %				70 %				50 %				30 %				0 %			
	上方光束 7 %		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
下方光束	92 %	床		10 %				10 %				10 %				10 %				0 %		
室指数	照明率 ( X0.01 )																				ZCM	
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	
下方投影面積	等価発光面積	c m <sup>2</sup>																				
		c m <sup>2</sup>																				
取付高さ	器具間隔最大限		H m																			
	横方向 ( A )	縦方向 ( B )	H m																			
H m		0.74 H m	0.74 H m	H m																		
H m		H m																				
H m		H m																				
H m		H m																				
H m		H m																				
H m		H m																				
H m		H m																				

