

屋内照明器具特性	
品番 (品名)	XND2066WBK
光源	LED4000_85_1635 x1 1635.0lm
管理番号	K0176639 (0) DB1
BZ分類	BZ1

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		0 %	室指数	照明率 (X0.01)																			ZCM	
下方光束		100 %																						
保守率		良	0.81	0.6	87	81	78	75	86	81	78	75	85	80	77	75	84	80	77	75	74			
		中	0.77	0.8	92	88	84	82	92	87	84	82	90	86	84	82	89	86	83	81	80			
		否	0.68	1.0	96	92	89	86	95	91	88	86	93	90	88	86	92	89	87	85	84			
下方投影面積		c m ²	1.25	98	95	92	90	98	94	92	90	96	93	91	89	94	92	90	89	87				
			1.5	100	97	94	92	99	96	94	92	98	95	93	91	96	94	92	91	89				
等価発光面積		c m ²	2.0	102	100	97	96	101	99	97	95	100	97	96	94	98	96	95	93	92				
			2.5	104	101	99	98	103	101	99	97	101	99	98	96	99	98	96	95	93				
取付高さ	器具間隔最大限		3.0	104	102	101	99	103	102	100	99	101	100	99	98	100	98	97	96	94				
	横方向 (A)	縦方向 (B)	4.0	105	104	103	101	104	103	102	101	102	101	100	99	100	100	99	98	96				
H m	0.77 H m	0.77 H m	5.0	106	105	104	103	105	104	103	102	103	102	101	100	101	100	100	99	97				
			7.0	107	106	105	104	106	105	104	103	104	103	102	101	102	101	101	100	98				
			10.0	107	107	106	105	106	106	105	105	104	104	103	103	102	102	101	101	98				

