

| 屋内照明器具特性             |           |                                                      |                     |                                    |                 |  |  |  |   |  |  |  |   |  |  |  |   |  |   |  |   |
|----------------------|-----------|------------------------------------------------------|---------------------|------------------------------------|-----------------|--|--|--|---|--|--|--|---|--|--|--|---|--|---|--|---|
| 品番 (品名)              |           | YYY66502                                             |                     |                                    |                 |  |  |  |   |  |  |  |   |  |  |  |   |  |   |  |   |
| 光源                   |           | LDA7L - G - E17 / K60E / S / W/ 2 ×1760.0 lm         |                     |                                    |                 |  |  |  |   |  |  |  |   |  |  |  |   |  |   |  |   |
| 管理番号                 |           | K0186818 ( 0 ) DB 1                                  |                     |                                    |                 |  |  |  |   |  |  |  |   |  |  |  |   |  |   |  |   |
| B Z 分類               |           | BZ10 / 0.9 / BZ9 / 1.4 / BZ8 / 1.8 / BZ7 / 4.5 / BZ6 |                     |                                    |                 |  |  |  |   |  |  |  |   |  |  |  |   |  |   |  |   |
| 器具効率<br>上方光束<br>下方光束 |           | 6 %<br>1 %<br>5 %                                    | 反射率                 | 天井                                 | %               |  |  |  | % |  |  |  | % |  |  |  | % |  |   |  | % |
|                      |           |                                                      |                     | 壁                                  |                 |  |  |  |   |  |  |  |   |  |  |  |   |  | % |  |   |
|                      |           |                                                      |                     | 床                                  | %               |  |  |  | % |  |  |  | % |  |  |  | % |  |   |  | % |
|                      |           |                                                      |                     | 室指数                                | 照明率 ( X0.01)ZCM |  |  |  |   |  |  |  |   |  |  |  |   |  |   |  |   |
| 保守率                  |           | 良<br>中<br>否                                          | 0.63<br>0.6<br>0.56 | 0.6<br>0.8<br>1.0<br>1.25          |                 |  |  |  |   |  |  |  |   |  |  |  |   |  |   |  |   |
|                      |           |                                                      | 下方投影面積<br>等価発光面積    | cm <sup>2</sup><br>cm <sup>2</sup> | 1.5<br>2.0      |  |  |  |   |  |  |  |   |  |  |  |   |  |   |  |   |
| 取付<br>高さ             | 器具間隔最大限   |                                                      |                     | 2.5                                |                 |  |  |  |   |  |  |  |   |  |  |  |   |  |   |  |   |
|                      | 横方向 ( A ) |                                                      | 縦方向 ( B )           | 3.0                                |                 |  |  |  |   |  |  |  |   |  |  |  |   |  |   |  |   |
| H m                  | 0.00 H m  | 0.20 H m                                             |                     | 4.0                                |                 |  |  |  |   |  |  |  |   |  |  |  |   |  |   |  |   |
|                      |           |                                                      |                     | 5.0                                |                 |  |  |  |   |  |  |  |   |  |  |  |   |  |   |  |   |
|                      |           |                                                      |                     | 7.0                                |                 |  |  |  |   |  |  |  |   |  |  |  |   |  |   |  |   |
|                      |           |                                                      |                     | 10.0                               |                 |  |  |  |   |  |  |  |   |  |  |  |   |  |   |  |   |

