

|          |   |
|----------|---|
| 屋内照明器具特性 |   |
| 品番 (品名)  | XS Z B 1 6 3 6 7                              |
| 光源       | LLD2401VCB1 ×1                      500.0 l m |
| 管理番号     | K0193060 ( 0 ) DB 1                           |
| B Z 分類   | BZ6   |

|        |                           |          |               |     |     |     |      |     |     |     |      |     |     |     |      |     |     |     |     |     |
|--------|---------------------------|----------|---------------|-----|-----|-----|------|-----|-----|-----|------|-----|-----|-----|------|-----|-----|-----|-----|-----|
| 器具効率   | 82 %                      | 天井       | 80 %          |     |     |     | 70 % |     |     |     | 50 % |     |     |     | 30 % |     |     |     | 0 % |     |
|        |                           | 壁        | 70            | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 0 % |     |
| 上方光束   | 25 %                      | 床        | 10 %          |     |     |     | 10 % |     |     |     | 10 % |     |     |     | 10 % |     |     |     | 0 % |     |
| 下方光束   | 57 %                      | 室指数      | 照明率 ( X0.01 ) |     |     |     |      |     |     |     |      |     |     |     |      |     |     |     | ZCM |     |
| 保守率    | 良 0.63<br>中 0.6<br>否 0.56 | 0.6      | 4.2           | 3.2 | 2.6 | 2.1 | 4.0  | 3.1 | 2.5 | 2.1 | 3.5  | 2.8 | 2.3 | 1.9 | 3.1  | 2.5 | 2.1 | 1.8 | 1.5 |     |
|        |                           | 0.8      | 4.9           | 3.9 | 3.3 | 2.8 | 4.6  | 3.7 | 3.1 | 2.7 | 4.1  | 3.4 | 2.9 | 2.5 | 3.6  | 3.1 | 2.6 | 2.3 | 1.9 |     |
|        |                           | 1.0      | 5.4           | 4.4 | 3.8 | 3.3 | 5.1  | 4.2 | 3.6 | 3.2 | 4.5  | 3.8 | 3.3 | 2.9 | 4.0  | 3.4 | 3.0 | 2.7 | 2.2 |     |
|        |                           | 1.25     | 5.8           | 5.0 | 4.3 | 3.8 | 5.5  | 4.7 | 4.1 | 3.7 | 4.9  | 4.2 | 3.8 | 3.4 | 4.3  | 3.8 | 3.4 | 3.1 | 2.6 |     |
| 下方投影面積 | c m <sup>2</sup>          | 1.5      | 6.1           | 5.3 | 4.7 | 4.2 | 5.8  | 5.1 | 4.5 | 4.1 | 5.1  | 4.6 | 4.1 | 3.7 | 4.6  | 4.1 | 3.7 | 3.4 | 2.8 |     |
|        |                           | 2.0      | 6.6           | 5.9 | 5.3 | 4.8 | 6.2  | 5.6 | 5.1 | 4.6 | 5.5  | 5.0 | 4.6 | 4.3 | 4.9  | 4.5 | 4.2 | 3.9 | 3.2 |     |
| 取付高さ   | 器具間隔最大限                   |          | 2.5           | 6.8 | 6.2 | 5.7 | 5.3  | 6.5 | 5.9 | 5.5 | 5.1  | 5.8 | 5.4 | 5.0 | 4.6  | 5.2 | 4.8 | 4.5 | 4.2 | 3.5 |
|        | 横方向 (A)                   | 縦方向 (B)  | 3.0           | 7.1 | 6.5 | 6.0 | 5.6  | 6.7 | 6.2 | 5.8 | 5.4  | 6.0 | 5.6 | 5.2 | 4.9  | 5.3 | 5.0 | 4.7 | 4.5 | 3.8 |
| H m    | 0.94 H m                  | 0.94 H m | 4.0           | 7.3 | 6.9 | 6.5 | 6.1  | 7.0 | 6.5 | 6.2 | 5.9  | 6.2 | 5.9 | 5.6 | 5.4  | 5.6 | 5.3 | 5.1 | 4.9 | 4.1 |
|        |                           |          | 5.0           | 7.5 | 7.1 | 6.8 | 6.4  | 7.1 | 6.8 | 6.5 | 6.2  | 6.4 | 6.1 | 5.9 | 5.6  | 5.7 | 5.5 | 5.3 | 5.1 | 4.3 |
|        |                           |          | 7.0           | 7.7 | 7.4 | 7.1 | 6.9  | 7.3 | 7.1 | 6.8 | 6.6  | 6.6 | 6.4 | 6.2 | 6.0  | 5.9 | 5.8 | 5.6 | 5.4 | 4.6 |
|        |                           |          | 10.0          | 7.9 | 7.6 | 7.4 | 7.2  | 7.5 | 7.3 | 7.1 | 6.9  | 6.8 | 6.6 | 6.5 | 6.3  | 6.1 | 6.0 | 5.8 | 5.7 | 4.8 |

