

| 屋内照明器具特性 |                             |
|----------|-----------------------------|
| 品番 (品名)  | XND2508WLZ                  |
| 光源       | LED3000_85_2285 x1 2285.0lm |
| 管理番号     | K0176484 ( 0 ) DB 1         |
| BZ分類     | BZ1                         |

|                      |                                    |         |               |      |     |     |     |      |     |     |     |      |     |     |     |      |     |     |     |     |
|----------------------|------------------------------------|---------|---------------|------|-----|-----|-----|------|-----|-----|-----|------|-----|-----|-----|------|-----|-----|-----|-----|
| 器具効率<br>上方光束<br>下方光束 | 101 %<br>0 %<br>101 %              | 反射率     | 天井            | 80 % |     |     |     | 70 % |     |     |     | 50 % |     |     |     | 30 % |     |     |     | 0 % |
|                      |                                    | 壁       | 床             | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 0 % |
|                      |                                    | 室指数     | 照明率 ( X0.01 ) | ZCM  |     |     |     |      |     |     |     |      |     |     |     |      |     |     |     |     |
| 保守率                  | 良 0.81                             | 0.6     | 77            | 70   | 65  | 61  | 76  | 69   | 64  | 61  | 75  | 68   | 64  | 61  | 73  | 68   | 64  | 61  | 60  |     |
|                      | 中 0.77                             | 0.8     | 85            | 78   | 74  | 70  | 84  | 78   | 73  | 70  | 82  | 77   | 73  | 70  | 81  | 76   | 72  | 70  | 68  |     |
|                      | 否 0.68                             | 1.0     | 90            | 84   | 80  | 76  | 89  | 83   | 79  | 76  | 87  | 82   | 79  | 76  | 85  | 81   | 78  | 75  | 74  |     |
| 下方投影面積<br>等価発光面積     | cm <sup>2</sup><br>cm <sup>2</sup> | 1.25    | 94            | 89   | 85  | 82  | 93  | 88   | 84  | 81  | 91  | 87   | 84  | 81  | 89  | 86   | 83  | 80  | 79  |     |
|                      |                                    | 1.5     | 97            | 92   | 88  | 85  | 96  | 91   | 88  | 85  | 93  | 90   | 87  | 84  | 92  | 88   | 86  | 84  | 82  |     |
|                      |                                    | 2.0     | 100           | 96   | 93  | 90  | 99  | 95   | 92  | 90  | 97  | 94   | 91  | 89  | 95  | 92   | 90  | 88  | 86  |     |
| 取付高さ<br>Hm           | 器具間隔最大限                            |         | 2.5           | 102  | 99  | 96  | 94  | 101  | 98  | 95  | 93  | 98   | 96  | 94  | 92  | 96   | 94  | 93  | 91  |     |
|                      | 横方向 (A)                            | 縦方向 (B) | 3.0           | 103  | 100 | 98  | 96  | 102  | 99  | 97  | 95  | 100  | 98  | 96  | 94  | 98   | 96  | 94  | 93  |     |
|                      | Hm                                 | Hm      | 4.0           | 105  | 102 | 101 | 99  | 103  | 101 | 100 | 98  | 101  | 100 | 98  | 97  | 99   | 98  | 97  | 96  |     |
|                      |                                    |         | 5.0           | 105  | 104 | 102 | 101 | 104  | 103 | 101 | 100 | 102  | 101 | 100 | 98  | 100  | 99  | 98  | 97  |     |
|                      |                                    |         | 7.0           | 106  | 105 | 104 | 103 | 105  | 104 | 103 | 102 | 103  | 102 | 101 | 100 | 101  | 100 | 99  | 99  |     |
|                      |                                    |         | 10.0          | 107  | 106 | 105 | 105 | 106  | 105 | 104 | 104 | 104  | 103 | 103 | 102 | 102  | 101 | 101 | 100 |     |

