

屋内照明器具特性	
品番 (品名)	X N W0 6 6 2 W N
光源	L E D 5 0 0 0 _ 8 5 _ 5 6 5 × 1 5 6 5 . 0 l m
管理番号	K 0 1 8 3 3 1 1 (0) D B 1
B Z 分類	B Z 1

器具効率		1 0 0 % 上方光束 0 % 下方光束 1 0 0 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
			室指数	照明率 (X 0 . 0 1) Z C M																		
保守率		良 中 否	0 . 6	8 5	7 9	7 5	7 2	8 4	7 8	7 5	7 2	8 3	7 8	7 4	7 2	8 1	7 7	7 4	7 2	7 1		
			0 . 8	9 1	8 5	8 2	7 9	9 0	8 5	8 1	7 9	8 8	8 4	8 1	7 9	8 7	8 3	8 1	7 8	7 7		
			1 . 0	9 4	9 0	8 6	8 4	9 3	8 9	8 6	8 4	9 2	8 8	8 5	8 3	9 0	8 7	8 5	8 3	8 2		
			0 . 6 8	1 . 2 5	9 7	9 3	9 0	8 8	9 6	9 2	9 0	8 7	9 5	9 1	8 9	8 7	9 3	9 0	8 8	8 6	8 5	
下方投影面積		c m ²	1 . 5	9 9	9 5	9 3	9 0	9 8	9 5	9 2	9 0	9 6	9 3	9 1	8 9	9 5	9 2	9 0	8 9	8 7		
等価発光面積			c m ²	2 . 0	1 0 1	9 8	9 6	9 4	1 0 0	9 8	9 5	9 4	9 9	9 6	9 4	9 3	9 7	9 5	9 3	9 2	9 0	
取付 高さ	器具間隔最大限		2 . 5	1 0 3	1 0 0	9 8	9 7	1 0 2	1 0 0	9 8	9 6	1 0 0	9 8	9 6	9 5	9 8	9 6	9 5	9 4	9 2		
	横方向 (A) 縦方向 (B)		3 . 0	1 0 4	1 0 2	1 0 0	9 8	1 0 3	1 0 1	9 9	9 8	1 0 1	9 9	9 8	9 6	9 9	9 8	9 6	9 5	9 3		
H m	0 . 7 9 H m 0 . 7 9 H m		4 . 0	1 0 5	1 0 3	1 0 2	1 0 0	1 0 4	1 0 2	1 0 1	1 0 0	1 0 2	1 0 1	9 9	9 8	1 0 0	9 9	9 8	9 7	9 5		
			5 . 0	1 0 6	1 0 4	1 0 3	1 0 2	1 0 5	1 0 3	1 0 2	1 0 1	1 0 2	1 0 1	1 0 1	1 0 0	1 0 1	1 0 0	9 9	9 8	9 6		
			7 . 0	1 0 7	1 0 5	1 0 5	1 0 4	1 0 5	1 0 4	1 0 4	1 0 3	1 0 3	1 0 2	1 0 2	1 0 1	1 0 1	1 0 1	1 0 0	9 9	9 7		
			1 0 . 0	1 0 7	1 0 6	1 0 6	1 0 5	1 0 6	1 0 5	1 0 5	1 0 4	1 0 4	1 0 3	1 0 3	1 0 2	1 0 2	1 0 1	1 0 1	1 0 0	9 8		

