

屋内照明器具特性	
品番 (品名)	XND2509BVZ
光源	LED3500_85_2250 ×1 2250.0 lm
管理番号	K0176488 (0) DB 1
BZ分類	BZ1

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																
保守率		良 中 否	0.81	0.6	75	67	62	58	74	66	62	58	72	66	61	58	71	65	61	58	56
			0.77	0.8	84	77	72	68	83	76	72	68	81	75	71	68	79	74	71	68	66
			0.68	1.0	89	83	79	75	88	82	78	75	86	81	78	75	84	80	77	74	73
				1.25	93	88	84	81	92	87	84	81	90	86	83	80	88	85	82	80	78
下方投影面積		cm ²	1.5	96	91	87	85	95	90	87	84	93	89	86	84	91	88	85	83	81	
			2.0	99	95	92	90	98	95	92	89	96	93	91	88	94	91	89	88	86	
等価発光面積		cm ²	2.5	101	98	95	93	100	97	95	92	98	95	93	91	96	94	92	90	88	
			3.0	102	100	97	95	101	99	97	95	99	97	95	94	97	95	94	92	90	
H _m	1.10H _m	1.10H _m	4.0	104	102	100	98	103	101	99	98	101	99	98	96	98	97	96	95	93	
			5.0	105	103	102	100	104	102	101	99	101	100	99	98	99	98	97	96	94	
			7.0	106	105	103	102	105	104	102	101	102	101	100	100	100	100	99	98	96	
			10.0	107	106	105	104	105	105	104	103	103	103	102	101	101	101	100	100	97	

