

# 屋内照明器具特性

|         |                     |           |
|---------|---------------------|-----------|
| 品番 (品名) | XS Z D 1 0 6 9 N    |           |
| 光源      | LLD2411NCB1 ×1      | 500.0 l m |
| 管理番号    | K0192046 ( 0 ) DB 1 |           |
| B Z 分類  | B Z 1               |           |

|        |                   |                  |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |       |    |
|--------|-------------------|------------------|------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|-------|----|
| 器具効率   | 81 %              | 天井               | 80 % |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |       |    |
|        | 上方光束              |                  | 0 %  | 70 | 50 | 30 | 10   | 70 | 50 | 30 | 10   | 70 | 50 | 30 | 10   | 70 | 50 | 30 | 10  | 0 %   |    |
| 下方光束   | 81 %              | 床                | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |       |    |
| 室指数    | 照明率 ( X 0 . 0 1 ) |                  |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     | Z C M |    |
| 保守率    | 良                 | 0.67             | 0.6  | 74 | 71 | 69 | 67   | 74 | 71 | 69 | 67   | 73 | 70 | 69 | 67   | 72 | 70 | 68 | 67  | 67    |    |
|        | 中                 | 0.63             | 0.8  | 78 | 75 | 73 | 71   | 77 | 74 | 72 | 71   | 76 | 74 | 72 | 71   | 75 | 73 | 72 | 71  | 70    |    |
|        | 否                 | 0.56             | 1.0  | 80 | 77 | 75 | 74   | 79 | 77 | 75 | 74   | 78 | 76 | 74 | 73   | 77 | 75 | 74 | 73  | 72    |    |
| 下方投影面積 | 等価発光面積            | c m <sup>2</sup> | 1.25 | 81 | 79 | 77 | 76   | 81 | 78 | 77 | 76   | 79 | 78 | 76 | 75   | 78 | 77 | 76 | 75  | 74    |    |
|        |                   |                  | 1.5  | 82 | 80 | 79 | 77   | 82 | 80 | 78 | 77   | 80 | 79 | 77 | 76   | 79 | 78 | 77 | 76  | 75    | 75 |
| 取付高さ   | 器具間隔最大限           |                  | 2.0  | 84 | 82 | 80 | 79   | 83 | 81 | 80 | 79   | 81 | 80 | 79 | 78   | 80 | 79 | 78 | 78  | 76    |    |
|        | 横方向 ( A )         | 縦方向 ( B )        | 2.5  | 84 | 83 | 82 | 81   | 84 | 82 | 81 | 80   | 82 | 81 | 80 | 79   | 81 | 80 | 79 | 79  | 77    |    |
| H m    | 0.80 H m          | 0.80 H m         | 3.0  | 85 | 84 | 83 | 82   | 84 | 83 | 82 | 81   | 83 | 82 | 81 | 80   | 81 | 80 | 80 | 80  | 79    | 78 |
|        |                   |                  | 4.0  | 85 | 84 | 84 | 83   | 85 | 84 | 83 | 82   | 83 | 82 | 82 | 81   | 82 | 81 | 81 | 81  | 80    | 78 |
|        |                   |                  | 5.0  | 86 | 85 | 84 | 84   | 85 | 84 | 84 | 83   | 83 | 83 | 82 | 82   | 82 | 81 | 81 | 81  | 79    | 79 |
|        |                   |                  | 7.0  | 86 | 86 | 85 | 85   | 85 | 85 | 84 | 84   | 84 | 83 | 83 | 83   | 82 | 82 | 82 | 81  | 79    | 79 |
|        |                   |                  | 10.0 | 87 | 86 | 86 | 85   | 86 | 85 | 85 | 85   | 84 | 84 | 83 | 83   | 82 | 82 | 82 | 82  | 80    | 80 |

