

屋内照明器具特性

品番 (品名)	XS Z D 1 0 6 9 V	
光源	LLD2411VCB1 ×1	500.0 l m
管理番号	K0192046 (0) DB 1	
B Z 分類	B Z 1	

器具効率	81 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束		0 %	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束	81 %	床	10 %				10 %				10 %				10 %				0 %	
室指数	照明率 (X 0 . 0 1)																			Z C M
保守率	良	0.67	0.6	74	71	69	67	74	71	69	67	73	70	69	67	72	70	68	67	67
	中	0.63	0.8	78	75	73	71	77	74	72	71	76	74	72	71	75	73	72	71	70
	否	0.56	1.0	80	77	75	74	79	77	75	74	78	76	74	73	77	75	74	73	72
下方投影面積	等価発光面積	c m ²	1.25	81	79	77	76	81	78	77	76	79	78	76	75	78	77	76	75	74
			1.5	82	80	79	77	82	80	78	77	80	79	77	76	79	78	77	76	75
取付高さ	器具間隔最大限		2.0	84	82	80	79	83	81	80	79	81	80	79	78	80	79	78	78	76
	横方向 (A)	縦方向 (B)	2.5	84	83	82	81	84	82	81	80	82	81	80	79	81	80	79	79	77
H m	0.80 H m	0.80 H m	3.0	85	84	83	82	84	83	82	81	83	82	81	80	81	80	80	79	78
			4.0	85	84	84	83	85	84	83	82	83	82	82	81	82	81	81	81	80
			5.0	86	85	84	84	85	84	84	83	83	83	82	82	82	81	81	81	79
			7.0	86	86	85	85	85	85	84	84	84	83	83	83	82	82	82	81	79
			10.0	87	86	86	85	86	85	85	85	84	84	83	83	82	82	82	82	80

