

屋内照明器具特性

品番 (品名)	XS Z D 3 0 0 0 L	
光源	LLD3400LCB1 ×1	700.0 1 m
管理番号	K0191487 (0) DB 1	
B Z 分類	BZ3 / 0.7 / BZ2	

器具効率	96 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	96 %	室指数	照明率 (X0.01)																ZCM	
保守率	良 中 否 0.67 0.63 0.56	0.6	63	54	47	43	62	53	47	43	60	52	47	43	59	51	46	43	41	
		0.8	74	65	59	55	72	64	59	55	70	63	58	54	68	62	58	54	53	
		1.0	80	72	67	63	79	72	66	63	76	70	66	62	74	69	65	62	60	
		1.25	85	78	73	69	84	78	73	69	81	76	72	69	79	75	71	68	67	
下方投影面積	c m ²	1.5	88	82	78	74	87	81	77	74	85	80	76	73	82	78	75	73	71	
		2.0	92	87	84	80	91	87	83	80	89	85	82	79	87	83	81	78	76	
取付高さ	器具間隔最大限		2.5	95	91	87	85	93	90	87	84	91	88	85	83	89	86	84	82	80
	横方向 (A)	縦方向 (B)	3.0	96	93	90	87	95	92	89	87	93	90	88	86	91	88	86	85	82
H m	1.31 H m	1.31 H m	4.0	98	96	93	91	97	95	93	91	95	93	91	89	93	91	89	88	86
			5.0	100	97	95	94	98	96	95	93	96	94	93	91	94	93	91	90	88
			7.0	101	99	98	96	100	98	97	96	97	96	95	94	95	94	93	92	90
			10.0	102	101	100	99	101	100	99	98	99	98	97	96	96	96	96	95	94

