

# 屋内照明器具特性

品番 (品名)	XS Z D 3 0 0 1 V	
光源	LLD3401VCB1 ×1	700.0 1 m
管理番号	K0191441 ( 0 ) DB 1	
B Z 分類	BZ2 / 8.5 / BZ1	

器具効率	90 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	90 %	室指数	照明率 ( X0.01 )																ZCM	
保守率	良	0.67	0.6	61	52	46	42	60	51	46	42	58	51	46	42	56	50	45	42	41
	中	0.63	0.8	70	62	57	53	69	62	57	53	67	61	56	53	65	60	56	53	51
	否	0.56	1.0	76	69	64	61	75	68	64	60	73	67	63	60	71	66	63	60	58
			1.25	80	75	70	67	79	74	70	67	77	73	69	66	75	71	68	66	64
下方投影面積		cm <sup>2</sup>	1.5	83	78	74	71	82	77	74	71	80	76	73	70	78	75	72	70	68
等価発光面積		cm <sup>2</sup>	2.0	87	83	79	77	86	82	79	76	84	81	78	75	82	79	77	75	73
取付高さ	器具間隔最大限		2.5	89	86	83	80	88	85	82	80	86	83	81	79	84	82	80	78	76
	横方向 (A)	縦方向 (B)	3.0	91	88	85	83	89	87	84	82	87	85	83	81	85	83	82	80	78
H m	1.26 H m	1.26 H m	4.0	92	90	88	86	91	89	87	86	89	87	86	84	87	86	84	83	81
			5.0	93	91	90	88	92	91	89	88	90	89	87	86	88	87	86	85	83
			7.0	95	93	92	91	93	92	91	90	91	90	89	88	89	89	88	87	85
			10.0	95	94	93	93	94	93	93	92	92	92	91	90	90	90	89	89	86

