

屋内照明器具特性

品番 (品名)	XS Z D 3 0 2 1 N	
光源	LLD3421NCB1 × 1	700.0 1 m
管理番号	K0191444 (0) DB 1	
B Z 分類	B Z 1	

器具効率	92 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束 0 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
下方光束	92 %	床		10 %				10 %				10 %				10 %				0 %	
室指数	照明率 (X 0.01)																			Z C M	
保守率	良 0.67	0.6	0.6	76	70	66	64	75	70	66	64	74	69	66	64	73	69	66	63	62	
	中 0.63		0.8	82	77	73	71	81	76	73	71	80	76	73	70	79	75	72	70	69	
	否 0.56		1.0	86	81	78	75	85	81	77	75	83	80	77	75	82	79	76	74	73	
下方投影面積	c m ²	等価発光面積	c m ²	1.25	89	85	82	79	88	84	81	79	86	83	81	79	85	82	80	78	77
				1.5	91	87	84	82	90	87	84	82	88	85	83	81	86	84	82	81	79
取付高さ	器具間隔最大限		2.5	95	92	90	88	94	91	90	88	92	90	88	87	90	89	87	86	84	
	横方向 (A)	縦方向 (B)	3.0	96	94	92	90	95	93	91	90	93	91	90	89	91	90	89	88	86	
H m	0.41 H m	0.41 H m	4.0	97	95	94	93	96	94	93	92	94	93	92	91	92	91	90	89	87	
			5.0	98	96	95	94	97	95	94	93	95	94	93	92	93	92	91	91	88	
			7.0	98	97	97	96	97	96	96	95	95	95	94	93	93	93	92	92	90	
			10.0	99	98	98	97	98	97	97	96	96	95	95	95	94	94	93	93	90	

