

屋内照明器具特性

品番 (品名)	XS Z D 3 0 6 3 L	
光源	LLD3410LCB1 ×1	700.0 1 m
管理番号	K0192043 (0) DB 1	
BZ分類	BZ1	

器具効率	86 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束		0 %	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束	86 %	床	10 %				10 %				10 %				10 %				0 %	
室指数	照明率 (X 0.01)																			ZCM
保守率	良	0.67	0.6	78	74	72	70	77	74	71	70	77	73	71	70	76	73	71	70	69
	中	0.63	0.8	82	78	76	74	81	78	76	74	80	77	75	74	79	77	75	74	73
	否	0.56	1.0	84	81	79	77	83	81	78	77	82	80	78	77	81	79	77	76	75
下方投影面積	等価発光面積	cm ²	1.25	86	83	81	80	85	83	81	79	84	82	80	79	83	81	80	78	77
			1.5	87	85	83	81	86	84	82	81	85	83	82	80	84	82	81	80	79
取付高さ	器具間隔最大限		2.0	89	87	85	84	88	86	85	83	86	85	84	83	85	84	83	82	80
	横方向 (A)	縦方向 (B)	2.5	90	88	86	85	89	87	86	85	87	86	85	84	86	85	84	83	81
Hm	0.81Hm	0.81Hm	3.0	90	89	87	86	89	88	87	86	88	87	86	85	86	85	85	84	82
			4.0	91	90	89	88	90	89	88	87	88	88	87	86	87	86	86	86	85
			5.0	91	91	90	89	91	90	89	88	89	88	88	87	87	87	86	84	
			7.0	92	91	91	90	91	90	90	89	89	89	88	88	88	87	87	86	84
			10.0	92	92	91	91	91	91	91	90	90	89	89	89	88	88	87	87	85

