

屋内照明器具特性	
品番 (品名)	XND9067WW
光源	LED4000_80_9880 ×1 9880.0lm
管理番号	K0179588 (1) DB1
BZ分類	BZ1

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z CM
保守率		良 中 否	0.76	0.6	75	68	62	59	75	67	62	59	73	66	62	59	71	66	62	59	57
			0.72	0.8	83	76	71	68	82	76	71	68	81	75	71	68	79	74	70	67	66
			0.64	1.0	88	82	77	74	87	81	77	74	85	80	76	73	83	79	76	73	71
				1.25	92	87	82	79	91	86	82	79	89	85	81	78	87	83	80	78	76
下方投影面積		cm ²	1.5	95	90	86	83	94	89	85	82	91	88	84	82	89	86	83	81	79	
			2.0	98	94	91	88	97	93	90	87	95	92	89	87	93	90	88	86	84	
等価発光面積		cm ²	2.5	100	97	94	91	99	96	93	91	97	94	92	90	95	92	90	89	87	
			3.0	101	98	96	94	100	98	95	93	98	96	94	92	96	94	92	91	89	
H m	1.11 H m	1.11 H m	4.0	103	101	99	97	102	100	98	96	100	98	96	95	98	96	95	93	91	
			5.0	104	102	100	99	103	101	100	98	101	99	98	97	99	97	96	95	93	
			7.0	105	104	103	101	104	103	102	100	102	101	100	99	100	99	98	97	95	
			10.0	106	105	104	103	105	104	103	102	103	102	101	101	100	99	99	99	96	

