

| 屋内照明器具特性 |                                |
|----------|--------------------------------|
| 品番 (品名)  | XND9097SN                      |
| 光源       | LED5000_80_10355 ×1 10355.0 lm |
| 管理番号     | K0179649 ( 0 ) DB 1            |
| BZ分類     | BZ1                            |

| 器具効率     |           | 100 %           | 反射率             | 天井            | 80 % |     |     |     | 70 % |     |     |     | 50 % |     |     |     | 30 % |    |    |    | 0 % |    |    |
|----------|-----------|-----------------|-----------------|---------------|------|-----|-----|-----|------|-----|-----|-----|------|-----|-----|-----|------|----|----|----|-----|----|----|
|          |           |                 |                 | 壁             | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50 | 30 | 10 | 0 % |    |    |
|          |           |                 |                 | 床             | 10 % |     |     |     | 10 % |     |     |     | 10 % |     |     |     | 10 % |    |    |    | 0 % |    |    |
| 上方光束     |           | 0 %             | 室指数             | 照明率 ( X0.01 ) |      |     |     |     |      |     |     |     |      |     |     |     |      |    |    |    |     | Z  | CM |
| 下方光束     |           |                 |                 | 100 %         |      |     |     |     |      |     |     |     |      |     |     |     |      |    |    |    |     |    |    |
| 保守率      |           | 良<br>中<br>否     | 0.76            | 0.6           | 71   | 63  | 57  | 53  | 70   | 62  | 57  | 53  | 69   | 61  | 56  | 53  | 67   | 61 | 56 | 53 | 51  |    |    |
|          |           |                 | 0.72            | 0.8           | 81   | 73  | 68  | 64  | 80   | 72  | 67  | 64  | 78   | 71  | 67  | 63  | 76   | 70 | 66 | 63 | 62  |    |    |
|          |           |                 | 0.64            | 1.0           | 86   | 80  | 75  | 71  | 85   | 79  | 74  | 71  | 83   | 78  | 74  | 70  | 81   | 77 | 73 | 70 | 68  |    |    |
|          |           |                 |                 | 1.25          | 91   | 85  | 81  | 77  | 90   | 84  | 80  | 77  | 88   | 83  | 79  | 76  | 86   | 82 | 78 | 76 | 74  |    |    |
| 下方投影面積   |           | cm <sup>2</sup> | 1.5             | 94            | 89   | 85  | 81  | 93  | 88   | 84  | 81  | 91  | 86   | 83  | 80  | 89  | 85   | 82 | 80 | 78 |     |    |    |
| 等価発光面積   |           |                 | cm <sup>2</sup> | 2.0           | 98   | 93  | 90  | 87  | 97   | 93  | 89  | 87  | 94   | 91  | 88  | 86  | 92   | 89 | 87 | 85 | 83  |    |    |
| 取付<br>高さ | 器具間隔最大限   |                 | 2.5             | 100           | 96   | 93  | 91  | 99  | 95   | 93  | 90  | 96  | 94   | 91  | 89  | 94  | 92   | 90 | 88 | 86 |     |    |    |
|          | 横方向 ( A ) |                 | 縦方向 ( B )       |               | 3.0  | 101 | 98  | 96  | 93   | 100 | 97  | 95  | 93   | 98  | 96  | 93  | 92   | 96 | 94 | 92 | 91  | 88 |    |
| H m      | 1.15 H m  | 1.15 H m        | 4.0             | 103           | 101  | 99  | 97  | 102 | 100  | 98  | 96  | 100 | 98   | 96  | 95  | 98  | 96   | 95 | 93 | 91 |     |    |    |
|          |           |                 | 5.0             | 104           | 102  | 101 | 99  | 103 | 101  | 100 | 98  | 101 | 99   | 98  | 97  | 99  | 97   | 96 | 95 | 93 |     |    |    |
|          |           |                 | 7.0             | 105           | 104  | 103 | 101 | 104 | 103  | 102 | 101 | 102 | 101  | 100 | 99  | 100 | 99   | 98 | 97 | 95 |     |    |    |
|          |           |                 | 10.0            | 106           | 105  | 104 | 103 | 105 | 104  | 103 | 102 | 103 | 102  | 101 | 101 | 100 | 99   | 99 | 99 | 96 |     |    |    |

