

屋内照明器具特性	
品番 (品名)	X S L G 1 0 5 V S
光源	LED3500_70_360 ×1 360.0 lm
管理番号	K0171432 (0) DB 1
B Z 分類	BZ9 / 0.9 / BZ8

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																
保守率		良 中 否	0.63	0.6	44	32	24	18	40	29	22	17	33	24	18	14	26	20	15	11	6
			0.6	0.8	53	40	32	26	48	37	30	24	39	31	25	20	31	25	20	16	9
			0.56	1.0	59	47	38	32	54	43	35	30	44	36	30	25	35	29	24	20	12
				1.25	64	53	45	38	59	49	41	35	48	41	35	30	39	33	28	24	15
下方投影面積 等価発光面積		c m ²		1.5	68	58	50	43	62	53	46	40	51	44	39	34	41	36	32	28	18
				2.0	74	65	57	51	68	60	53	48	56	50	45	40	45	41	37	33	22
				2.5	78	70	63	57	71	64	58	53	59	54	49	45	48	44	40	37	25
				3.0	80	73	67	62	74	67	62	57	62	57	52	48	50	46	43	40	27
H m	1.59 H m	2.09 H m		4.0	84	78	72	68	77	72	67	63	65	61	57	54	53	50	47	44	30
				5.0	86	81	76	72	79	75	71	67	67	63	60	57	55	52	50	47	33
				7.0	89	85	81	78	82	79	75	72	69	67	64	62	57	55	53	51	36
				10.0	91	88	85	82	84	82	79	77	72	69	67	65	60	58	56	55	39

