

屋内照明器具特性	
品番 (品名)	XS Z P 7 3 0 5 N
光源	LLD3400NCB1+LLD2400NCB1 ×1 1200.0 1m
管理番号	K0192199(0)DB1
BZ分類	BZ3/1.1/BZ2/1.8/BZ3

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	42%	反射率	床	10%				10%				10%				10%				0%
下方光束	58%		室指数	照明率 (X0.01)																ZCM
保守率	良 中 否	0.69	0.6	56	45	38	34	52	43	37	33	46	39	34	30	40	35	31	28	24
		0.67	0.8	65	55	49	44	61	52	46	42	54	47	42	39	47	42	39	36	30
			1.0	71	62	56	51	67	59	53	49	59	53	48	45	52	47	44	41	35
		0.63	1.25	76	68	62	58	72	65	59	55	63	58	54	51	55	52	49	46	38
下方投影面積	c m ²	1.5	80	73	67	63	75	69	64	60	66	61	58	55	58	55	52	49	41	
		2.0	84	79	74	70	79	74	70	67	70	66	63	60	61	59	56	54	45	
取付高さ	器具間隔最大限		2.5	87	82	78	75	82	78	74	71	73	69	67	64	64	61	59	57	47
	横方向 (A)	縦方向 (B)	3.0	89	85	81	78	84	80	77	74	74	71	69	67	65	63	61	60	49
H m	1.33 H m	1.33 H m	4.0	92	88	85	83	86	84	81	79	76	74	72	70	67	65	64	63	51
			5.0	93	90	88	86	88	85	83	81	78	76	74	73	68	67	66	65	52
			7.0	95	93	91	89	90	88	86	85	79	78	77	75	69	68	68	67	54
			10.0	96	95	93	92	91	89	88	87	80	79	78	78	70	70	69	68	55

