

屋内照明器具特性	
品番 (品名)	XS Z P 7 3 0 7 L
光源	LLD3401LCB1+LLD2401LCB1 ×1 1200.0 1m
管理番号	K0192199(0)DB1
BZ分類	BZ3/1.1/BZ2/1.8/BZ3

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	42%	反射率	10%				10%				10%				10%				0%	
下方光束	58%		床	10%				10%				10%				10%				0%
		室指数	照明率 (X0.01)																ZCM	
保守率	良	0.69	0.6	5.6	4.5	3.8	3.4	5.2	4.3	3.7	3.3	4.6	3.9	3.4	3.0	4.0	3.5	3.1	2.8	2.4
	中	0.67	0.8	6.5	5.5	4.9	4.4	6.1	5.2	4.6	4.2	5.4	4.7	4.2	3.9	4.7	4.2	3.9	3.6	3.0
	否	0.63	1.0	7.1	6.2	5.6	5.1	6.7	5.9	5.3	4.9	5.9	5.3	4.8	4.5	5.2	4.7	4.4	4.1	3.5
			1.25	7.6	6.8	6.2	5.8	7.2	6.5	5.9	5.5	6.3	5.8	5.4	5.1	5.5	5.2	4.9	4.6	3.8
下方投影面積		c m ²	1.5	8.0	7.3	6.7	6.3	7.5	6.9	6.4	6.0	6.6	6.1	5.8	5.5	5.8	5.5	5.2	4.9	4.1
等価発光面積		c m ²	2.0	8.4	7.9	7.4	7.0	7.9	7.4	7.0	6.7	7.0	6.6	6.3	6.0	6.1	5.9	5.6	5.4	4.5
取付高さ	器具間隔最大限		2.5	8.7	8.2	7.8	7.5	8.2	7.8	7.4	7.1	7.3	6.9	6.7	6.4	6.4	6.1	5.9	5.7	4.7
	横方向 (A)	縦方向 (B)	3.0	8.9	8.5	8.1	7.8	8.4	8.0	7.7	7.4	7.4	7.1	6.9	6.7	6.5	6.3	6.1	6.0	4.9
H m	1.33 H m	1.33 H m	4.0	9.2	8.8	8.5	8.3	8.6	8.4	8.1	7.9	7.6	7.4	7.2	7.0	6.7	6.5	6.4	6.3	5.1
			5.0	9.3	9.0	8.8	8.6	8.8	8.5	8.3	8.1	7.8	7.6	7.4	7.3	6.8	6.7	6.6	6.5	5.2
			7.0	9.5	9.3	9.1	8.9	9.0	8.8	8.6	8.5	7.9	7.8	7.7	7.5	6.9	6.8	6.8	6.7	5.4
			10.0	9.6	9.5	9.3	9.2	9.1	8.9	8.8	8.7	8.0	7.9	7.8	7.8	7.0	7.0	6.9	6.8	5.5

