

屋内照明器具特性	
品番 (品名)	XSZR1011N
光源	LLD2401NCB1 ×1                      500.0 lm
管理番号	K0192057(0)DB1
BZ分類	BZ1/4.5/BZ2/6.0/BZ1

器具効率	64%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	64%	室指数	照明率 ( X0.01)                      ZCM																	
保守率	良 0.63 中 0.6 否 0.56	0.6	45	40	36	34	45	40	36	34	44	39	36	34	43	39	36	34	33	
		0.8	51	46	43	40	51	46	43	40	49	45	42	40	48	45	42	40	39	
		1.0	55	50	47	45	54	50	47	45	53	49	46	44	51	48	46	44	43	
		1.25	58	54	51	49	57	53	51	48	55	52	50	48	54	52	49	48	47	
下方投影面積	cm <sup>2</sup>	1.5	59	56	53	51	59	55	53	51	57	55	52	51	56	54	52	50	49	
		2.0	62	59	57	55	61	58	56	55	60	57	56	54	58	56	55	54	52	
取付高さ	器具間隔最大限		2.5	63	61	59	57	62	60	58	57	61	59	58	56	60	58	57	56	54
	横方向 (A)	縦方向 (B)	3.0	64	62	60	59	63	62	60	59	62	60	59	58	61	59	58	57	56
Hm	1.07Hm	1.07Hm	4.0	65	64	62	61	65	63	62	61	63	62	61	60	62	61	60	59	58
			5.0	66	65	64	63	65	64	63	62	64	63	62	61	62	61	60	59	59
			7.0	67	66	65	64	66	65	64	64	65	64	63	63	63	63	62	62	60
			10.0	67	67	66	66	67	66	65	65	65	65	64	64	64	63	63	63	61

