

屋内照明器具特性

品番 (品名)	XSZR1011V														
光源	LLD2401VCB1 ×1 500.0 lm														
管理番号	K0192057(0)DB1														
BZ分類	BZ1/4.5/BZ2/6.0/BZ1														

器具効率	64%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	0%	室指数	照明率 (X0.01)																ZCM		
下方光束	64%																				
保守率	良 中 否 0.63 0.6 0.56	0.6	45	40	36	34	45	40	36	34	44	39	36	34	43	39	36	34	33		
		0.8	51	46	43	40	51	46	43	40	49	45	42	40	48	45	42	40	39		
		1.0	55	50	47	45	54	50	47	45	53	49	46	44	51	48	46	44	43		
		1.25	58	54	51	49	57	53	51	48	55	52	50	48	54	52	49	48	47		
下方投影面積	c m ²	1.5	59	56	53	51	59	55	53	51	57	55	52	51	56	54	52	50	49		
		2.0	62	59	57	55	61	58	56	55	60	57	56	54	58	56	55	54	52		
取付高さ	器具間隔最大限		2.5	63	61	59	57	62	60	58	57	61	59	58	56	60	58	57	56		
	横方向 (A)	縦方向 (B)	3.0	64	62	60	59	63	62	60	59	62	60	59	58	61	59	58	57		
H m	1.07 H m	1.07 H m	4.0	65	64	62	61	65	63	62	61	63	62	61	60	62	61	60	59		
			5.0	66	65	64	63	65	64	63	62	64	63	62	61	62	62	61	60	59	
			7.0	67	66	65	64	66	65	64	64	65	64	63	63	63	63	62	60		
			10.0	67	67	66	66	67	66	65	65	65	65	64	64	64	63	63	61		

