

# 屋内照明器具特性

品番 (品名)	XSZR1020N	
光源	LLD2420NCB1 ×1	500.0 l m
管理番号	K0192053 (0) DB1	
BZ分類	BZ1	

器具効率	87 %	天井	80 %				70 %				50 %				30 %				0 %	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0 %	反射率	10 %				10 %				10 %				10 %				0 %	
下方光束	87 %		室指数	照明率 ( X0.01)																ZCM
保守率	良 0.63	0.6	0.6	69	63	59	57	69	63	59	57	67	62	59	57	66	62	59	56	55
	中 0.6	0.6	0.8	75	70	66	64	74	70	66	64	73	69	66	63	72	68	65	63	62
	否 0.56	0.6	1.0	79	74	71	68	78	74	70	68	77	73	70	68	75	72	69	67	66
下方投影面積	cm <sup>2</sup>	1.25	82	78	75	72	81	77	74	72	79	76	74	72	78	75	73	71	70	
		1.5	84	80	77	75	83	80	77	75	81	78	76	74	80	77	75	74	72	
等価発光面積	cm <sup>2</sup>	2.0	86	83	81	79	86	83	81	79	84	81	80	78	82	80	79	77	76	
		2.5	88	85	83	82	87	85	83	81	85	83	82	80	84	82	81	79	78	
取付高さ	器具間隔最大限		3.0	89	87	85	83	88	86	84	83	86	85	83	82	84	83	82	81	79
H m	0.55 H m	0.55 H m	4.0	90	89	87	86	89	88	86	85	87	86	85	84	86	85	84	83	81
			5.0	91	90	88	87	90	89	88	87	88	87	86	85	86	85	85	84	82
			7.0	92	91	90	89	91	90	89	88	89	88	87	87	87	87	86	85	83
			10.0	92	92	91	90	91	91	90	90	89	89	89	88	88	87	87	87	84

