

# 屋内照明器具特性

品番 (品名)	XSZR1020V	
光源	LLD2420VCB1 ×1	500.0 l m
管理番号	K0192053 ( 0 ) DB 1	
BZ分類	BZ1	

器具効率	87 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束		0 %	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束	87 %	床	10 %				10 %				10 %				10 %				0 %	
室指数	照明率 ( X0.01 )																			ZCM
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56
下方投影面積	等価発光面積	cm <sup>2</sup>	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	82	84	86	88	89	90	91	92	92
		cm <sup>2</sup>	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	82	84	86	88	89	90	91	92	92	92
取付高さ	器具間隔最大限		2.5	3.0	4.0	5.0	7.0	10.0	82	84	86	88	89	90	91	92	92	92	92	92
H m	横方向 ( A )	縦方向 ( B )	0.55 H m	0.55 H m	0.55 H m	0.55 H m	0.55 H m	0.55 H m	0.55 H m	0.55 H m	0.55 H m	0.55 H m	0.55 H m	0.55 H m	0.55 H m	0.55 H m	0.55 H m	0.55 H m	0.55 H m	0.55 H m
	0.55 H m	0.55 H m	0.55 H m	0.55 H m	0.55 H m	0.55 H m	0.55 H m	0.55 H m	0.55 H m	0.55 H m	0.55 H m	0.55 H m	0.55 H m	0.55 H m	0.55 H m	0.55 H m	0.55 H m	0.55 H m	0.55 H m	0.55 H m

