

屋内照明器具特性

品番 (品名)	XSZR1040V	
光源	LLD2420VCB1 ×1	500.0 l m
管理番号	K0192053 (0) DB1	
BZ分類	BZ1	

器具効率	87 %	天井	80 %				70 %				50 %				30 %				0 %																																																																																																																							
	上方光束		0 %	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																																																																																																																						
下方光束	87 %	床	10 %				10 %				10 %				10 %				0 %																																																																																																																							
室指数	照明率 (X0.01)																			ZCM																																																																																																																						
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6																																																																																																																						
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6																																																																																																																						
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56																																																																																																																						
下方投影面積	等価発光面積	cm ²	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0																																																																																																																															
			cm ²	82	84	86	88	89	90	91	92	92	69	75	79	82	84	86	87	88	89	90	91	92	63	70	74	78	80	83	85	86	87	88	89	90	91	92	59	66	71	75	77	80	83	84	85	86	87	88	89	90	91	92	57	64	68	72	74	77	80	81	82	83	84	85	86	87	88	89	90	91	92	69	74	78	81	83	85	86	87	88	89	90	91	92	63	66	68	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	59	63	65	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89

