

# 屋内照明器具特性

品番 (品名)	XSZR1070V	
光源	LLD2410VCB1 ×1	500.0 lm
管理番号	K0192052(0)DB1	
BZ分類	BZ1	

器具効率	91%	天井	80%				70%				50%				30%				0%									
	上方光束		0%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%								
下方光束	91%	床	10%				10%				10%				10%				0%									
室指数	照明率 (X0.01)																			ZCM								
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6								
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6								
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56								
下方投影面積	等価発光面積	cm <sup>2</sup>	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	71	64	60	57	70	63	59	57	68	63	59	56	67	62	59	56	55
			1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	85	80	77	74	84	80	77	74	82	79	76	74	81	78	75	73	72	
取付高さ	器具間隔最大限		2.5	3.0	4.0	5.0	7.0	10.0	92	89	87	85	91	88	86	84	89	87	85	83	87	85	84	82	81			
	横方向 (A)	縦方向 (B)	3.0	4.0	5.0	7.0	10.0	93	90	88	87	92	90	88	86	90	88	86	85	88	87	85	84	82				
Hm	0.75Hm	0.75Hm	4.0	5.0	7.0	10.0	94	92	91	89	93	91	90	89	91	90	89	87	89	88	87	86	84					
			5.0	7.0	10.0	95	93	92	91	94	93	91	90	92	91	90	89	90	89	88	88	88	85					
			7.0	10.0	96	95	94	93	95	94	93	92	93	92	91	91	91	90	90	89	89	87						
			10.0	97	96	95	94	95	95	94	94	93	93	92	92	92	91	91	90	88								

