

# 屋内照明器具特性

品番 (品名)	XSZR3000L														
光源	LLD3400LCB1 ×1					700.0 1m									
管理番号	K0192054(0)DB1														
BZ分類	BZ2														

器具効率	70%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	0%	室指数	照明率 (X0.01)																ZCM		
下方光束	70%																				
保守率	良 中 否 0.63 0.6 0.56	0.6	4.8	4.2	3.8	3.5	4.8	4.1	3.7	3.5	4.6	4.1	3.7	3.5	4.5	4.0	3.7	3.5	3.3		
		0.8	5.5	4.9	4.5	4.2	5.4	4.8	4.5	4.2	5.2	4.8	4.4	4.2	5.1	4.7	4.4	4.2	4.0		
		1.0	5.9	5.3	5.0	4.7	5.8	5.3	4.9	4.7	5.6	5.2	4.9	4.6	5.5	5.1	4.8	4.6	4.5		
		1.25	6.2	5.7	5.4	5.1	6.1	5.7	5.4	5.1	5.9	5.6	5.3	5.1	5.8	5.5	5.2	5.0	4.9		
下方投影面積	c m <sup>2</sup>	1.5	6.4	6.0	5.7	5.4	6.3	5.9	5.6	5.4	6.2	5.8	5.6	5.4	6.0	5.7	5.5	5.3	5.2		
		2.0	6.7	6.4	6.1	5.9	6.6	6.3	6.0	5.8	6.4	6.2	6.0	5.8	6.3	6.1	5.9	5.7	5.6		
取付高さ	器具間隔最大限		2.5	6.9	6.6	6.3	6.1	6.8	6.5	6.3	6.1	6.6	6.4	6.2	6.0	6.4	6.3	6.1	6.0		
	横方向 (A)	縦方向 (B)	3.0	7.0	6.7	6.5	6.3	6.9	6.7	6.5	6.3	6.7	6.5	6.4	6.2	6.6	6.4	6.3	6.1		
H m	1.09 H m	1.09 H m	4.0	7.1	6.9	6.8	6.6	7.0	6.9	6.7	6.6	6.9	6.7	6.6	6.5	6.7	6.6	6.5			
			5.0	7.2	7.0	6.9	6.8	7.1	7.0	6.8	6.7	6.9	6.8	6.7	6.6	6.8	6.7	6.6			
			7.0	7.3	7.2	7.1	7.0	7.2	7.1	7.0	6.9	7.0	7.0	6.9	6.8	6.9	6.8	6.7			
			10.0	7.4	7.3	7.2	7.1	7.3	7.2	7.1	7.1	7.1	7.1	7.0	6.9	7.0	6.9	6.8			

