

屋内照明器具特性	
品番 (品名)	XSZR3000V
光源	LLD3400VCB1 ×1 700.0 l m
管理番号	K0192054 (0) DB 1
BZ分類	BZ2

器具効率	70 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	0 %	室指数	照明率 (X0.01)																ZCM	
下方光束	70 %																			
保守率	良	0.63	0.6	48	42	38	35	48	41	37	35	46	41	37	35	45	40	37	35	33
	中	0.6	0.8	55	49	45	42	54	48	45	42	52	48	44	42	51	47	44	42	40
	否	0.56	1.0	59	53	50	47	58	53	49	47	56	52	49	46	55	51	48	46	45
			1.25	62	57	54	51	61	57	54	51	59	56	53	51	58	55	52	50	49
下方投影面積		cm ²	1.5	64	60	57	54	63	59	56	54	62	58	56	54	60	57	55	53	52
等価発光面積		cm ²	2.0	67	64	61	59	66	63	60	58	64	62	60	58	63	61	59	57	56
取付高さ	器具間隔最大限		2.5	69	66	63	61	68	65	63	61	66	64	62	60	64	63	61	60	58
	横方向 (A)	縦方向 (B)	3.0	70	67	65	63	69	67	65	63	67	65	64	62	66	64	63	61	60
Hm	1.09Hm	1.09Hm	4.0	71	69	68	66	70	69	67	66	69	67	66	65	67	66	65	64	62
			5.0	72	70	69	68	71	70	68	67	69	68	67	66	68	67	66	65	63
			7.0	73	72	71	70	72	71	70	69	70	70	69	68	69	68	67	67	65
			10.0	74	73	72	71	73	72	71	71	71	71	70	69	70	69	69	68	66

