

屋内照明器具特性	
品番 (品名)	XSZR3001N
光源	LLD3401NCB1 ×1                      700.0 1 m
管理番号	K0192060 ( 0 ) DB 1
BZ分類	BZ1 / 3.5 / BZ2 / 6.0 / BZ1

器具効率	62 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	62 %	室指数	照明率 ( X0.01 )																ZCM	
保守率	良	0.63	0.6	4.4	3.9	3.5	3.3	4.4	3.9	3.5	3.3	4.3	3.8	3.5	3.3	4.2	3.8	3.5	3.3	3.2
	中	0.6	0.8	5.0	4.5	4.2	3.9	4.9	4.5	4.2	3.9	4.8	4.4	4.1	3.9	4.7	4.4	4.1	3.9	3.8
	否	0.56	1.0	5.4	4.9	4.6	4.4	5.3	4.9	4.6	4.4	5.2	4.8	4.5	4.3	5.0	4.7	4.5	4.3	4.2
			1.25	5.6	5.3	5.0	4.8	5.6	5.2	4.9	4.7	5.4	5.1	4.9	4.7	5.3	5.0	4.8	4.7	4.6
下方投影面積		cm <sup>2</sup>	1.5	5.8	5.5	5.2	5.0	5.7	5.4	5.2	5.0	5.6	5.3	5.1	5.0	5.5	5.3	5.1	4.9	4.8
等価発光面積		cm <sup>2</sup>	2.0	6.1	5.8	5.6	5.4	6.0	5.7	5.5	5.3	5.8	5.6	5.4	5.3	5.7	5.5	5.4	5.2	5.1
取付高さ	器具間隔最大限		2.5	6.2	6.0	5.8	5.6	6.1	5.9	5.7	5.6	6.0	5.8	5.6	5.5	5.8	5.7	5.6	5.5	5.3
	横方向 (A)	縦方向 (B)	3.0	6.3	6.1	5.9	5.8	6.2	6.0	5.9	5.7	6.1	5.9	5.8	5.7	5.9	5.8	5.7	5.6	5.5
Hm	1.07Hm	1.07Hm	4.0	6.4	6.3	6.1	6.0	6.3	6.2	6.1	5.9	6.2	6.1	6.0	5.9	6.1	6.0	5.9	5.8	5.6
			5.0	6.5	6.3	6.2	6.1	6.4	6.3	6.2	6.1	6.3	6.2	6.1	6.0	6.1	6.0	6.0	5.9	5.7
			7.0	6.6	6.5	6.4	6.3	6.5	6.4	6.3	6.2	6.3	6.3	6.2	6.1	6.2	6.1	6.1	6.0	5.9
			10.0	6.6	6.5	6.5	6.4	6.5	6.5	6.4	6.4	6.4	6.3	6.3	6.2	6.3	6.2	6.2	6.1	6.0

