

屋内照明器具特性	
品番 (品名)	XSZR3010N
光源	LLD3400NCB1 ×1 700.0 1 m
管理番号	K0192054 (0) DB 1
BZ分類	BZ2

器具効率	70 %	天井	80 %				70 %				50 %				30 %				0 %				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %				
下方光束	70 %	室指数	照明率 (X0.01)																				ZCM
保守率	良	0.63	0.6	48	42	38	35	48	41	37	35	46	41	37	35	45	40	37	35	33			
	中	0.6	0.8	55	49	45	42	54	48	45	42	52	48	44	42	51	47	44	42	40			
	否	0.56	1.0	59	53	50	47	58	53	49	47	56	52	49	46	55	51	48	46	45			
			1.25	62	57	54	51	61	57	54	51	59	56	53	51	58	55	52	50	49			
下方投影面積			1.5	64	60	57	54	63	59	56	54	62	58	56	54	60	57	55	53	52			
			2.0	67	64	61	59	66	63	60	58	64	62	60	58	63	61	59	57	56			
取付高さ	器具間隔最大限		2.5	69	66	63	61	68	65	63	61	66	64	62	60	64	63	61	60	58			
	横方向 (A)	縦方向 (B)	3.0	70	67	65	63	69	67	65	63	67	65	64	62	66	64	63	61	60			
Hm	1.09Hm	1.09Hm	4.0	71	69	68	66	70	69	67	66	69	67	66	65	67	66	65	64	62			
			5.0	72	70	69	68	71	70	68	67	69	68	67	66	68	67	66	65	63			
			7.0	73	72	71	70	72	71	70	69	70	70	69	68	69	68	67	67	65			
			10.0	74	73	72	71	73	72	71	71	71	71	70	69	70	69	69	68	66			

