

屋内照明器具特性

品番 (品名)	XSZR3070N	
光源	LLD3410NCB1 ×1	700.0 1m
管理番号	K0192055(0)DB1	
BZ分類	BZ1	

器具効率	90%	天井	80%				70%				50%				30%				0%																																					
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10																																						
上方光束	0%	反射率	照明率 (×0.01)																				ZCM																																	
下方光束	90%	室指数																																																						
保守率	良 0.63	0.6	0.6	70	63	59	56	69	63	59	56	68	62	58	56	66	61	58	56	54	0.6	77	71	67	64	76	70	66	64	74	69	66	63	73	69	66	63	62	1.0	81	75	72	69	80	75	71	69	78	74	71	68	77	73	70	68	67
	中 0.6	0.56	1.25	84	80	76	73	83	79	76	73	81	78	75	73	80	77	74	72	71	1.5	86	82	79	77	85	82	79	76	83	80	78	76	82	79	77	75	74	2.0	89	86	83	81	88	85	83	81	86	84	82	80	84	82	81	79	77
	否 0.56	2.5	91	88	86	84	90	87	85	83	88	86	84	82	86	84	83	81	80	3.0	92	89	87	86	91	89	87	85	89	87	85	84	87	86	84	83	81	4.0	93	91	90	88	92	90	89	88	90	89	88	86	88	87	86	85	83	
下方投影面積	cm ²	等価発光面積	cm ²	5.0	94	92	91	90	93	92	90	89	91	90	89	88	89	88	87	84	7.0	95	94	93	92	94	93	92	91	92	91	90	90	90	89	89	88	86	10.0	95	95	94	93	94	94	93	92	92	92	91	91	91	90	90	89	87
				取付	器具間隔最大限																																																			
高さ	横方向 (A)	縦方向 (B)																																																						
Hm	0.75Hm	0.75Hm																																																						

