

屋内照明器具特性

品番 (品名)	XSZR3071V	
光源	LLD3411VCB1 ×1	700.0 l m
管理番号	K0192061(0)DB1	
BZ分類	BZ1	

器具効率	87 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束 0 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束	87 %	床		10 %				10 %				10 %				10 %				0 %
室指数	照明率 (X0.01)																			ZCM
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56
下方投影面積	等価発光面積	cm ²	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	8.2	8.4	8.7	8.8	8.9	9.1	9.2	9.2	9.3
			82	84	87	88	89	91	92	92	92	93	78	80	84	86	89	89	90	90
取付高さ	器具間隔最大限		H m	0.75 H m	縦方向 (B)	0.75 H m	8.2	8.4	8.7	8.8	8.9	9.1	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2
	8.4	8.7					8.8	8.9	9.1	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2
4.0	5.0	7.0	10.0	8.2	8.4	8.7	8.8	8.9	9.1	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2

