

屋内照明器具特性	
品番 (品名)	XND3536SV
光源	LED3500_80_3880 x1 3880.0 lm
管理番号	K0179575 (0) DB 1
BZ分類	BZ1

器具効率		1 0 0 % 上方光束 0 % 下方光束 1 0 0 %	天井 壁 床	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				1 0 %				1 0 %				1 0 %				1 0 %				0 %	
		室指数	照明率 (X 0 . 0 1) Z C M																		
保守率		良 中 否	0 . 6	8 7	8 2	7 8	7 6	8 6	8 1	7 8	7 6	8 5	8 1	7 8	7 6	8 4	8 0	7 7	7 5	7 4	
			0 . 8	9 2	8 8	8 4	8 2	9 2	8 7	8 4	8 2	9 0	8 6	8 4	8 2	8 9	8 6	8 3	8 1	8 0	
			1 . 0	9 6	9 2	8 9	8 6	9 5	9 1	8 8	8 6	9 3	9 0	8 8	8 6	9 2	8 9	8 7	8 5	8 4	
			0 . 6 4	1 . 2 5	9 8	9 5	9 2	9 0	9 8	9 4	9 2	9 0	9 6	9 3	9 1	8 9	9 4	9 2	9 0	8 9	8 7
下方投影面積 等価発光面積		c m ² c m ²	1 . 5	1 0 0	9 7	9 4	9 2	9 9	9 6	9 4	9 2	9 7	9 5	9 3	9 1	9 6	9 4	9 2	9 1	8 9	
			2 . 0	1 0 2	1 0 0	9 7	9 6	1 0 1	9 9	9 7	9 5	9 9	9 7	9 6	9 4	9 8	9 6	9 5	9 3	9 2	
取付 高さ	器具間隔最大限		2 . 5	1 0 4	1 0 1	9 9	9 8	1 0 3	1 0 0	9 9	9 7	1 0 1	9 9	9 7	9 6	9 9	9 7	9 6	9 5	9 3	
	横方向 (A)	縦方向 (B)	3 . 0	1 0 4	1 0 2	1 0 1	9 9	1 0 3	1 0 2	1 0 0	9 9	1 0 1	1 0 0	9 9	9 7	1 0 0	9 8	9 7	9 6	9 4	
H m	0 . 8 1 H m	0 . 8 1 H m	4 . 0	1 0 5	1 0 4	1 0 3	1 0 1	1 0 4	1 0 3	1 0 2	1 0 1	1 0 2	1 0 1	1 0 0	9 9	1 0 0	9 9	9 9	9 8	9 6	
			5 . 0	1 0 6	1 0 5	1 0 4	1 0 3	1 0 5	1 0 4	1 0 3	1 0 2	1 0 3	1 0 2	1 0 1	1 0 0	1 0 1	1 0 0	9 9	9 9	9 7	
			7 . 0	1 0 7	1 0 6	1 0 5	1 0 4	1 0 6	1 0 5	1 0 4	1 0 3	1 0 4	1 0 3	1 0 2	1 0 1	1 0 2	1 0 1	1 0 0	1 0 0	9 7	
			1 0 . 0	1 0 7	1 0 7	1 0 6	1 0 5	1 0 6	1 0 6	1 0 5	1 0 4	1 0 4	1 0 4	1 0 3	1 0 3	1 0 2	1 0 2	1 0 1	1 0 1	9 8	

