

屋内照明器具特性

品番 (品名)	XND3559WW																
光源	LED4000_80_3990 x1 3990.0 1m																
管理番号	K0179655(0)DB1																
BZ分類	BZ2/0.7/BZ1/4.5/BZ2/6.0/BZ1																

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	0%	反射率	10%				10%				10%				10%				0%	
下方光束	100%		床	10%				10%				10%				10%				0%
		室指数	照明率 (X0.01) ZCM																	
保守率	良	0.76	0.6	71	62	56	52	70	62	56	52	68	61	56	52	67	60	55	52	51
	中	0.72	0.8	80	72	67	63	79	72	67	63	77	71	66	63	75	70	66	62	61
	否	0.64	1.0	86	79	74	70	85	78	74	70	83	77	73	70	81	76	72	69	68
			1.25	91	85	80	76	90	84	80	76	87	82	79	76	85	81	78	75	73
下方投影面積			1.5	94	88	84	81	92	87	83	80	90	86	82	80	88	85	82	79	77
			2.0	97	93	89	86	96	92	89	86	94	91	88	85	92	89	87	84	82
取付高さ	器具間隔最大限		2.5	100	96	93	90	98	95	92	90	96	93	91	89	94	92	90	88	86
	横方向 (A)	縦方向 (B)	3.0	101	98	95	93	100	97	95	92	98	95	93	91	96	93	92	90	88
Hm	1.29Hm	1.29Hm	4.0	103	101	98	96	102	100	98	96	100	98	96	94	97	96	94	93	91
			5.0	104	102	100	99	103	101	99	98	101	99	98	96	98	97	96	95	92
			7.0	105	104	103	101	104	103	102	100	102	101	100	99	100	99	98	97	94
			10.0	106	105	104	103	105	104	103	102	103	102	101	100	101	100	99	99	96

