

屋内照明器具特性

品番 (品名)	XWG462KGNJ (J YOUJ I)									
光源	LED5000_85_6420 x1 6420.0 1 m									
管理番号	K0178170 (0) D 1									
BZ分類	BZ5 / 0.9 / BZ4									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	100 %	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.81	0.6	5.7	4.5	3.8	3.2	5.6	4.5	3.7	3.2	5.4	4.4	3.7	3.2	5.1	4.3	3.6	3.2	3.0
	中	0.77	0.8	6.8	5.6	4.9	4.3	6.6	5.6	4.8	4.3	6.3	5.4	4.8	4.3	6.1	5.3	4.7	4.2	4.0
	否	0.68	1.0	7.4	6.4	5.6	5.1	7.3	6.3	5.6	5.1	7.0	6.2	5.5	5.0	6.7	6.0	5.4	5.0	4.8
			1.25	8.1	7.1	6.4	5.9	7.9	7.0	6.4	5.8	7.6	6.8	6.3	5.8	7.3	6.7	6.2	5.7	5.5
下方投影面積			1.5	8.5	7.6	7.0	6.4	8.3	7.5	6.9	6.4	8.0	7.3	6.8	6.3	7.7	7.2	6.7	6.3	6.1
			2.0	9.0	8.3	7.8	7.3	8.9	8.2	7.7	7.3	8.6	8.0	7.6	7.2	8.3	7.8	7.4	7.1	6.8
取付高さ	器具間隔最大限		2.5	9.4	8.8	8.3	7.9	9.2	8.7	8.2	7.8	8.9	8.5	8.1	7.7	8.7	8.3	7.9	7.6	7.4
	横方向 (A)	縦方向 (B)	3.0	9.6	9.1	8.7	8.3	9.5	9.0	8.6	8.2	9.2	8.8	8.4	8.1	8.9	8.6	8.3	8.0	7.7
1.5m	2m	2.2m	4.0	9.9	9.5	9.2	8.8	9.8	9.4	9.1	8.8	9.5	9.2	8.9	8.6	9.2	9.0	8.7	8.5	8.2
2	2.64	2.73	5.0	10.1	9.8	9.5	9.2	10.0	9.7	9.4	9.1	9.7	9.4	9.2	9.0	9.4	9.2	9.0	8.8	8.6
2.5	3.27	3.3	7.0	10.3	10.1	9.8	9.6	10.2	9.9	9.7	9.5	9.9	9.7	9.5	9.4	9.7	9.5	9.4	9.2	8.9
3	3.91	3.87	10.0	10.5	10.3	10.1	10.0	10.3	10.2	10.0	9.9	10.1	9.9	9.8	9.7	9.8	9.7	9.6	9.5	9.2

