

屋内照明器具特性	
品番 (品名)	XND3566SN
光源	LED5000_80_3995 x1 3995.0 lm
管理番号	K0179571 (0) DB 1
BZ分類	BZ1

器具効率		100 %	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束		0 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束		100 %		照明率 (X0.01) ZCM																	
保守率		良 中 否	0.6	79	71	67	63	78	71	66	63	76	70	66	63	75	69	66	63	62	
			0.8	86	80	76	72	85	79	75	72	84	79	75	72	82	78	74	72	70	
			1.0	91	85	81	78	90	85	81	78	88	84	80	78	86	83	80	77	76	
			0.64	1.25	95	90	86	83	94	89	86	83	92	88	85	82	90	87	84	82	80
下方投影面積		cm ²	1.5	97	93	89	87	96	92	89	86	94	91	88	86	92	89	87	85	83	
			2.0	100	97	94	91	99	96	93	91	97	94	92	90	95	93	91	89	87	
等価発光面積		cm ²	2.5	102	99	96	94	101	98	96	94	99	96	94	93	97	95	93	92	90	
			3.0	103	100	98	96	102	100	98	96	100	98	96	95	98	96	95	93	91	
H _m	0.70H _m	0.70H _m	4.0	104	102	101	99	103	101	100	98	101	100	98	97	99	98	97	96	93	
			5.0	105	104	102	101	104	103	101	100	102	101	100	99	100	99	98	97	95	
			7.0	106	105	104	103	105	104	103	102	103	102	101	100	101	100	99	99	96	
			10.0	107	106	105	104	106	105	104	103	104	103	102	101	101	100	100	99	97	

