

# 屋内照明器具特性

|         |                                 |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|---------|---------------------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | XY2890K                         |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 光源      | LDA4L-H-E17/E/S/W/2 ×1 440.0 lm |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0176847(2)DR1                  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ10                            |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

|        |                 |         |                 |      |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |
|--------|-----------------|---------|-----------------|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 器具効率   | 59%             | 反射率     | 天井              | 80%  |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |     |     |
|        |                 |         | 壁               | 70   | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0%  |     |     |
|        |                 |         | 床               | 10%  |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0%  |     |     |
| 上方光束   | 27%             | 室指数     | 照明率 (X0.01) ZCM |      |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |
| 下方光束   | 32%             |         |                 |      |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |
| 保守率    | 良<br>中<br>否     | 0.63    | 0.6             | 0.56 | 0.6 | 2.5 | 1.7 | 1.2 | 0.8 | 2.2 | 1.5 | 1.1 | 0.8 | 1.8 | 1.3 | 0.9 | 0.6 | 1.4 | 1.0 | 0.7 | 0.4 | 0.1 |
|        |                 | 0.6     | 0.8             | 2.9  | 2.1 | 1.6 | 1.2 | 2.7 | 2.0 | 1.5 | 1.1 | 2.2 | 1.6 | 1.2 | 0.9 | 1.7 | 1.3 | 1.0 | 0.7 | 0.4 | 0.1 | 0.3 |
|        |                 | 0.56    | 1.0             | 3.3  | 2.5 | 2.0 | 1.6 | 3.0 | 2.3 | 1.8 | 1.4 | 2.4 | 1.9 | 1.5 | 1.2 | 1.9 | 1.5 | 1.2 | 0.9 | 0.5 | 0.2 | 0.5 |
|        |                 |         | 1.25            | 3.6  | 2.9 | 2.3 | 1.9 | 3.3 | 2.6 | 2.1 | 1.8 | 2.7 | 2.2 | 1.8 | 1.5 | 2.1 | 1.7 | 1.4 | 1.2 | 0.6 | 0.3 | 0.6 |
| 下方投影面積 | cm <sup>2</sup> | 1.5     | 3.8             | 3.2  | 2.6 | 2.2 | 3.5 | 2.9 | 2.4 | 2.0 | 2.9 | 2.4 | 2.0 | 1.7 | 2.3 | 1.9 | 1.6 | 1.4 | 0.8 | 0.4 | 0.8 |     |
| 等価発光面積 |                 | 2.0     | 4.2             | 3.6  | 3.1 | 2.7 | 3.8 | 3.3 | 2.9 | 2.5 | 3.2 | 2.8 | 2.4 | 2.1 | 2.6 | 2.2 | 2.0 | 1.7 | 1.1 | 0.5 | 1.1 |     |
| 取付高さ   | 器具間隔最大限         |         | 2.5             | 4.4  | 3.9 | 3.4 | 3.0 | 4.1 | 3.6 | 3.2 | 2.8 | 3.4 | 3.0 | 2.7 | 2.4 | 2.8 | 2.5 | 2.2 | 2.0 | 1.3 | 1.3 |     |
|        | 横方向 (A)         | 縦方向 (B) | 3.0             | 4.6  | 4.1 | 3.7 | 3.3 | 4.2 | 3.8 | 3.4 | 3.1 | 3.5 | 3.2 | 2.9 | 2.6 | 2.9 | 2.6 | 2.4 | 2.2 | 1.4 | 1.4 |     |
| Hm     | 0.00Hm          | 0.00Hm  | 4.0             | 4.8  | 4.4 | 4.0 | 3.7 | 4.5 | 4.1 | 3.8 | 3.5 | 3.8 | 3.5 | 3.2 | 3.0 | 3.1 | 2.9 | 2.7 | 2.5 | 1.7 | 1.7 |     |
|        |                 |         | 5.0             | 5.0  | 4.6 | 4.3 | 4.0 | 4.6 | 4.3 | 4.0 | 3.7 | 3.9 | 3.6 | 3.4 | 3.2 | 3.2 | 3.0 | 2.8 | 2.7 | 1.9 | 1.9 |     |
|        |                 |         | 7.0             | 5.1  | 4.9 | 4.6 | 4.4 | 4.8 | 4.5 | 4.3 | 4.1 | 4.1 | 3.9 | 3.7 | 3.5 | 3.4 | 3.2 | 3.1 | 3.0 | 2.1 | 2.1 |     |
|        |                 |         | 10.0            | 5.3  | 5.1 | 4.9 | 4.7 | 4.9 | 4.7 | 4.6 | 4.4 | 4.2 | 4.1 | 3.9 | 3.8 | 3.6 | 3.4 | 3.3 | 3.2 | 2.3 | 2.3 |     |

