

屋内照明器具特性	
品番 (品名)	XND3589SW
光源	LED4000_80_4000 ×1 4000.0 lm
管理番号	K0179663 (0) DB 1
BZ分類	BZ2 / 2.3 / BZ1 / 3.5 / BZ2 / 8.5 / BZ1

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
				室指数	照明率 (X 0 . 0 1) Z C M																				
保守率		良 中 否	0 . 7 6	0 . 6	7 0	6 1	5 5	5 1	6 9	6 1	5 5	5 1	6 7	6 0	5 5	5 1	6 6	5 9	5 4	5 1	4 9				
			0 . 7 2	0 . 8	7 9	7 1	6 6	6 2	7 8	7 1	6 5	6 2	7 6	7 0	6 5	6 1	7 4	6 9	6 4	6 1	5 9				
			0 . 6 4	1 . 0	8 5	7 8	7 3	6 9	8 4	7 7	7 2	6 9	8 2	7 6	7 2	6 8	8 0	7 5	7 1	6 8	6 6				
				1 . 2 5	9 0	8 4	7 9	7 5	8 9	8 3	7 9	7 5	8 7	8 2	7 8	7 5	8 5	8 0	7 7	7 4	7 2				
下方投影面積 等価発光面積		c m ²	1 . 5	9 3	8 8	8 3	8 0	9 2	8 7	8 3	7 9	9 0	8 5	8 2	7 9	8 8	8 4	8 1	7 8	7 6					
			2 . 0	9 7	9 3	8 9	8 6	9 6	9 2	8 8	8 5	9 4	9 0	8 7	8 5	9 1	8 8	8 6	8 4	8 2					
			2 . 5	9 9	9 6	9 3	9 0	9 8	9 5	9 2	8 9	9 6	9 3	9 0	8 8	9 4	9 1	8 9	8 7	8 5					
取付 高さ	器具間隔最大限		3 . 0	1 0 1	9 8	9 5	9 3	1 0 0	9 7	9 4	9 2	9 7	9 5	9 3	9 1	9 5	9 3	9 1	9 0	8 7					
	横方向 (A)	縦方向 (B)		1 0 3	1 0 0	9 8	9 6	1 0 2	9 9	9 7	9 5	9 9	9 7	9 6	9 4	9 7	9 6	9 4	9 3	9 0					
H m	1 . 3 0 H m	1 . 3 0 H m	4 . 0	1 0 4	1 0 2	1 0 0	9 8	1 0 3	1 0 1	9 9	9 8	1 0 0	9 9	9 7	9 6	9 8	9 7	9 6	9 5	9 2					
			5 . 0	1 0 5	1 0 4	1 0 2	1 0 1	1 0 4	1 0 3	1 0 1	1 0 0	1 0 2	1 0 1	1 0 0	9 9	1 0 0	9 9	9 8	9 7	9 4					
			7 . 0	1 0 6	1 0 5	1 0 4	1 0 3	1 0 5	1 0 4	1 0 3	1 0 2	1 0 3	1 0 2	1 0 1	1 0 0	1 0 1	1 0 0	9 9	9 9	9 6					
			1 0 . 0	1 0 6	1 0 5	1 0 4	1 0 3	1 0 5	1 0 4	1 0 3	1 0 2	1 0 3	1 0 2	1 0 1	1 0 0	1 0 1	1 0 0	9 9	9 9	9 6					

