

# 屋内照明器具特性

品番 (品名)	XS Z B 8 3 0 1 2	
光源	LLD2401LCB1 ×1	500.0 l m
管理番号	K0193246 ( 0 ) DB 1	
B Z 分類	BZ3 / 1.8 / BZ4 / 6.0 / BZ5	

器具効率	82 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束 16 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
下方光束	66 %	床		10 %				10 %				10 %				10 %				0 %	
室指数	照明率 ( X0.01 )																				ZCM
保守率	良	0.63	0.6	50	41	36	32	48	40	35	31	45	38	34	30	42	36	32	29	27	
	中	0.6	0.8	57	48	43	39	55	47	42	38	51	45	40	37	47	42	38	36	33	
	否	0.56	1.0	61	54	48	44	59	52	47	43	55	49	45	42	51	46	43	40	37	
			1.25	65	58	53	49	63	57	52	48	58	53	49	46	54	50	47	44	40	
下方投影面積	c m <sup>2</sup>		1.5	68	62	57	53	66	60	55	52	61	56	53	49	57	53	50	47	43	
等価発光面積	c m <sup>2</sup>		2.0	72	66	62	59	69	64	60	57	64	60	57	54	60	57	54	52	47	
取付高さ	器具間隔最大限		2.5	74	70	66	62	72	67	64	61	67	63	60	58	62	59	57	55	50	
	横方向 (A)	縦方向 (B)	3.0	76	72	68	65	73	70	66	64	68	65	63	60	63	61	59	57	52	
H m	1.07 H m	1.07 H m	4.0	78	75	72	69	75	72	70	67	70	68	66	64	65	63	62	60	55	
			5.0	79	77	74	72	77	74	72	70	72	70	68	66	67	65	64	62	56	
			7.0	81	79	77	75	78	76	75	73	73	72	70	69	68	67	66	65	59	
			10.0	82	81	79	78	80	78	77	75	74	73	72	71	69	68	68	67	60	

