

屋内照明器具特性	
品番 (品名)	XND9 9 9 4 S L Z
光源	LED3000_80_15165 ×1 15165.0 l m
管理番号	K0188257 (0) DB 1
B Z 分類	BZ1

器具効率		1 0 0 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %			
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %			
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %			
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																			Z C M	
下方光束		1 0 0 %																						
保守率		良	0 . 7 6	0 . 6	7 4	6 6	6 1	5 7	7 4	6 6	6 1	5 7	7 2	6 5	6 0	5 7	7 0	6 4	6 0	5 7	5 6			
		中	0 . 7 2	0 . 8	8 3	7 6	7 1	6 7	8 2	7 5	7 1	6 7	8 0	7 4	7 0	6 7	7 8	7 3	6 9	6 7	6 5			
		否	0 . 6 4	1 . 0	8 8	8 2	7 7	7 4	8 7	8 1	7 7	7 3	8 5	8 0	7 6	7 3	8 3	7 9	7 5	7 3	7 1			
				1 . 2 5	9 3	8 7	8 3	7 9	9 1	8 6	8 2	7 9	8 9	8 5	8 1	7 9	8 7	8 4	8 1	7 8	7 6			
下方投影面積		c m ²	1 . 5	9 5	9 0	8 7	8 3	9 4	9 0	8 6	8 3	9 2	8 8	8 5	8 2	9 0	8 7	8 4	8 2	8 0				
			2 . 0	9 9	9 5	9 2	8 9	9 8	9 4	9 1	8 8	9 5	9 2	9 0	8 8	9 3	9 1	8 9	8 7	8 5				
取付	器具間隔最大限			2 . 5	1 0 1	9 7	9 5	9 2	1 0 0	9 7	9 4	9 2	9 7	9 5	9 3	9 1	9 5	9 3	9 1	9 0	8 8			
高さ	横方向 (A)		縦方向 (B)	3 . 0	1 0 2	9 9	9 7	9 5	1 0 1	9 8	9 6	9 4	9 9	9 7	9 5	9 3	9 7	9 5	9 3	9 2	9 0			
H m	0 . 7 2 H m		0 . 7 2 H m	4 . 0	1 0 4	1 0 2	1 0 0	9 8	1 0 3	1 0 1	9 9	9 7	1 0 0	9 9	9 7	9 6	9 8	9 7	9 6	9 4	9 2			
				5 . 0	1 0 5	1 0 3	1 0 1	1 0 0	1 0 4	1 0 2	1 0 0	9 9	1 0 1	1 0 0	9 9	9 8	9 9	9 8	9 7	9 6	9 4			
				7 . 0	1 0 6	1 0 5	1 0 3	1 0 2	1 0 5	1 0 4	1 0 2	1 0 1	1 0 2	1 0 1	1 0 1	1 0 0	1 0 0	1 0 0	9 9	9 8	9 5			
				1 0 . 0	1 0 7	1 0 6	1 0 5	1 0 4	1 0 6	1 0 5	1 0 4	1 0 3	1 0 3	1 0 3	1 0 2	1 0 1	1 0 1	1 0 1	1 0 0	9 9	9 7			

