

屋内照明器具特性	
品番 (品名)	XND1035SYK
光源	LED2700_85_840 ×1 840.0 l m
管理番号	K0176633 (0) DB 1
BZ分類	BZ1

器具効率		1 0 1 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																		Z C M
下方光束		1 0 1 %																				
保守率		良	0 . 8 1	0 . 6	8 9	8 4	8 1	7 9	8 9	8 4	8 1	7 9	8 8	8 3	8 1	7 9	8 6	8 3	8 0	7 8	7 8	
		中	0 . 7 7	0 . 8	9 4	9 0	8 7	8 5	9 4	9 0	8 7	8 5	9 2	8 9	8 6	8 4	9 1	8 8	8 6	8 4	8 3	
		否	0 . 6 8	1 . 0	9 7	9 3	9 1	8 8	9 7	9 3	9 0	8 8	9 5	9 2	9 0	8 8	9 4	9 1	8 9	8 7	8 6	
				1 . 2 5	1 0 0	9 6	9 4	9 2	9 9	9 6	9 3	9 1	9 7	9 5	9 3	9 1	9 6	9 4	9 2	9 0	8 9	
下方投影面積		c m ²	1 . 5	1 0 1	9 8	9 6	9 4	1 0 1	9 8	9 5	9 4	9 9	9 7	9 5	9 3	9 7	9 5	9 4	9 2	9 1		
			2 . 0	1 0 3	1 0 1	9 9	9 7	1 0 3	1 0 0	9 8	9 7	1 0 1	9 9	9 7	9 6	9 9	9 7	9 6	9 5	9 3		
等価発光面積		c m ²	2 . 5	1 0 5	1 0 3	1 0 1	9 9	1 0 4	1 0 2	1 0 0	9 9	1 0 2	1 0 0	9 9	9 8	1 0 0	9 9	9 8	9 7	9 5		
取付高さ	器具間隔最大限			3 . 0	1 0 5	1 0 4	1 0 2	1 0 1	1 0 4	1 0 3	1 0 1	1 0 0	1 0 3	1 0 1	1 0 0	9 9	1 0 1	1 0 0	9 9	9 8		
	横方向 (A)		縦方向 (B)	4 . 0	1 0 6	1 0 5	1 0 4	1 0 3	1 0 5	1 0 4	1 0 3	1 0 2	1 0 3	1 0 2	1 0 1	1 0 0	1 0 1	1 0 1	1 0 0	9 9		
H m	0 . 4 4 H m		0 . 4 4 H m	5 . 0	1 0 7	1 0 6	1 0 5	1 0 4	1 0 6	1 0 5	1 0 4	1 0 3	1 0 4	1 0 3	1 0 2	1 0 2	1 0 2	1 0 1	1 0 1	9 8		
				7 . 0	1 0 8	1 0 7	1 0 6	1 0 5	1 0 7	1 0 6	1 0 5	1 0 4	1 0 5	1 0 4	1 0 3	1 0 3	1 0 3	1 0 2	1 0 2	1 0 1		
				1 0 . 0	1 0 8	1 0 8	1 0 7	1 0 6	1 0 7	1 0 7	1 0 6	1 0 5	1 0 5	1 0 5	1 0 4	1 0 4	1 0 3	1 0 3	1 0 2	9 9		

