

屋内照明器具特性	
品番 (品名)	XND9 9 4 1 F S K
光源	LED5000_80_17250 ×1 17250.0 lm
管理番号	K0188314 (0) D 1
BZ分類	BZ2/0.7/BZ1/3.5/BZ2/8.5/BZ1

器具効率		100 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
				室指数	照明率 (X0.01) ZCM																				
保守率		良 中 否	0.72	0.6	71	62	57	53	70	62	56	53	68	61	56	52	67	60	56	52	51				
			0.68	0.8	80	72	67	63	79	72	67	63	77	71	66	63	75	70	66	62	61				
			1.0	1.0	86	79	74	70	85	78	73	70	83	77	73	69	81	76	72	69	67				
			0.64	1.25	90	84	80	76	89	84	79	76	87	82	78	75	85	81	77	75	73				
下方投影面積 等価発光面積		cm ² cm ²	1.5	1.5	93	88	84	80	92	87	83	80	90	86	82	79	88	84	81	79	77				
			2.0	2.0	97	93	89	86	96	92	88	86	94	90	87	85	91	89	86	84	82				
			2.5	2.5	99	96	92	90	98	95	92	89	96	93	90	88	94	91	89	87	85				
取付 高さ	器具間隔最大限		3.0	101	98	95	92	100	97	94	92	97	95	93	91	95	93	91	90	87					
	横方向 (A)	縦方向 (B)																							
H _m	1.19 H _m	1.19 H _m	4.0	103	100	98	96	102	99	97	95	99	97	96	94	97	95	94	93	90					
			5.0	104	102	100	98	103	101	99	97	100	99	97	96	98	97	96	95	92					
			7.0	105	104	102	101	104	103	101	100	102	101	99	98	99	99	98	97	94					
			10.0	106	105	104	103	105	104	103	102	103	102	101	100	100	100	99	99	96					

